

## FREE-STAND, SINGLE OR DUAL ACCESS, TYPE 12



### INDUSTRY STANDARDS

UL 508A Listed; Type 12; File No. E61997  
cUL Listed per CSA C22.2 No. 94; Type 12; File No. E61997

NEMA/EEMAC Type 12  
E.I.A. RS310D  
CSA, File No. 42186, Type 12  
IEC 60529, IP55

### APPLICATION

Available with front or front and rear access, these Type 12 enclosures have sturdy unibody construction and flexible internal mounting options.

### SPECIFICATIONS

- 12 gauge steel
- Seams continuously welded and ground smooth; no holes or knockouts
- Stiffeners on back of two-door enclosures maintain flatness and increase rigidity
- Lifting eyes for easy handling
- 3-point latches operated by oil-tight key-locking handle
- Concealed, easy-to-remove hinges
- Data pockets are high-impact thermoplastic
- Internal mounting channels welded horizontally to sides at top, bottom and center
- Optional panels and rack mount angles can be mounted anywhere along channels
- Oil-resistant door gasket
- Bonding provision on door
- Provision for mounting fluorescent light

### FINISH

Two finishes available: ANSI 61 gray, polyester powder paint outside and inside; or ANSI 61 gray outside and white, polyester powder paint inside. Optional panels available with a white or conductive finish.

### ACCESSORIES

*See also Accessories.*

Plate Casters

Electric Heater

Door Stop Kit

Compact Cooling Fans

PANELITE Enclosure Lights Overview

*See also the Popular Cooling Products and Accessories tables following the Standard Products tables.*

### MODIFICATION AND CUSTOMIZATION

Hoffman excels at modifying and customizing products to your specifications. Contact your local Hoffman sales office or distributor for complete information.

**BULLETIN: A30**

Standard Product **One-Door Dual-Access**

| Catalog Number | AxBxC in.             | AxBxC mm         | Interior Finish | F (in.) | F (mm) | G (in.) | G (mm) | Number of Lifting Eyes | Number of Rack Units |
|----------------|-----------------------|------------------|-----------------|---------|--------|---------|--------|------------------------|----------------------|
| A722424FSDAG   | 72.06 x 24.06 x 24.06 | 1830 x 611 x 611 | Gray            | 38.03   | 966    | 29.12   | 740    | 2                      | 35                   |
| A722424FSDA    | 72.06 x 24.06 x 24.06 | 1830 x 611 x 611 | White           | 38.03   | 966    | 29.12   | 740    | 2                      | 35                   |
| A723024FSDAG   | 72.06 x 30.06 x 24.06 | 1830 x 764 x 611 | Gray            | 38.03   | 966    | 29.12   | 740    | 2                      | 35                   |
| A723024FSDA    | 72.06 x 30.06 x 24.06 | 1830 x 764 x 611 | White           | 38.03   | 996    | 29.12   | 740    | 2                      | 35                   |
| A723624FSDAG   | 72.06 x 36.06 x 24.06 | 1830 x 916 x 611 | Gray            | 38.03   | 966    | 29.12   | 740    | 2                      | 35                   |
| A723624FSDA    | 72.06 x 36.06 x 24.06 | 1830 x 916 x 611 | White           | 38.03   | 966    | 29.12   | 740    | 2                      | 35                   |
| A903624FSDAG   | 90.06 x 36.06 x 24.06 | 2288 x 916 x 611 | Gray            | 47.03   | 1195   | 38.12   | 968    | 2                      | 45                   |
| A903624FSDA    | 90.06 x 36.06 x 24.06 | 2288 x 916 x 611 | White           | 47.03   | 1195   | 38.12   | 968    | 2                      | 45                   |
| A722430FSDAG   | 72.06 x 24.06 x 30.06 | 1830 x 611 x 764 | Gray            | 38.03   | 966    | 29.12   | 740    | 4                      | 35                   |
| A722430FSDA    | 72.06 x 24.06 x 30.06 | 1830 x 611 x 764 | White           | 38.03   | 966    | 29.12   | 740    | 4                      | 35                   |
| A722436FSDAG   | 72.06 x 24.06 x 36.06 | 1830 x 611 x 916 | Gray            | 38.03   | 966    | 29.12   | 740    | 4                      | 35                   |
| A722436FSDA    | 72.06 x 24.06 x 36.06 | 1830 x 611 x 916 | White           | 38.03   | 966    | 29.12   | 740    | 4                      | 35                   |
| A723636FSDAG   | 72.06 x 36.06 x 36.06 | 1830 x 916 x 916 | Gray            | 38.03   | 966    | 29.12   | 740    | 4                      | 35                   |
| A723636FSDA    | 72.06 x 36.06 x 36.06 | 1830 x 916 x 916 | White           | 38.03   | 966    | 29.12   | 740    | 4                      | 35                   |
| A903636FSDAG   | 90.06 x 36.06 x 36.06 | 2288 x 916 x 916 | Gray            | 47.03   | 1195   | 38.12   | 968    | 4                      | 45                   |
| A903636FSDA    | 90.06 x 36.06 x 36.06 | 2288 x 916 x 916 | White           | 47.03   | 1195   | 38.12   | 968    | 4                      | 45                   |

Four lifting eyes are furnished if C = 30.06 (764mm) or more.

Removable 12.00 x 12.00 (305mm x 305mm) data pocket.

