

## SCREW-COVER GALVANIZED, TYPE 3R



8

### INDUSTRY STANDARDS

UL50, 50E Listed; Type 3R; File No. E27525  
cUL Listed per CSA C22.2 No 94; Type 3R; File No. E27525

NEMA/EEMAC Type 3R  
IEC 60529, IP32

### APPLICATION

Use this enclosure as a wiring or junction box to protect controls in outdoor applications requiring galvanized steel.

### FEATURES

- Drip-shield top and seam-free sides, front and back
- Slip-on removable cover fastened with plated steel screws along bottom edge
- Door handles on larger sides (body style C; see table)
- Embossed mounting holes on back of enclosure
- See table for knockout pattern
- Provision for padlocking
- No gasketing

### SPECIFICATIONS

- 16 or 14 gauge galvanized steel

### FINISH

Unpainted galvanized steel

### ACCESSORIES

See also Accessories.

Industrial Corrosion Inhibitors

Electric Heater

Grounding Device

Mounting Bracket Kit

BULLETIN: A90G3

### Standard Product

| Catalog Number | AxBxC in./mm                             | Body Style | D in./mm     | Mounting H in./mm | Mounting J in./mm | Knockout Pattern  |
|----------------|------------------------------------------|------------|--------------|-------------------|-------------------|-------------------|
| A4R44GV        | 4.00 x 4.00 x 4.00<br>102 x 102 x 120    | A          | —<br>—       | 1.88<br>48        | 2.00<br>51        | B-C               |
| A6R64GV        | 6.00 x 6.00 x 4.00<br>152 x 152 x 102    | A          | —<br>—       | 1.8<br>48         | 1.06<br>27        | B-C-D             |
| A8R84GV        | 8.00 x 8.00 x 4.00<br>203 x 203 x 102    | A          | —<br>—       | 2.25<br>57        | 1.06<br>27        | B-C-D             |
| A10R104GV      | 10.00 x 10.00 x 4.00<br>254 x 254 x 102  | A          | —<br>—       | 2.25<br>57        | 1.06<br>27        | C-D-E-F-G         |
| A12R124GV      | 12.00 x 12.00 x 4.00<br>305 x 305 x 102  | A          | —<br>—       | 2.25<br>57        | 1.06<br>27        | C-D-E-F-G         |
| A6R66GV        | 6.00 x 6.00 x 6.00<br>152 x 152 x 152    | A          | —<br>—       | 2.25<br>57        | 1.06<br>27        | B-C-D             |
| A8R86GV        | 8.00 x 8.00 x 6.00<br>203 x 203 x 152    | A          | —<br>—       | 2.25<br>57        | 1.06<br>27        | F-G-H-I           |
| A10R106GV      | 10.00 x 10.00 x 6.00<br>254 x 254 x 152  | A          | —<br>—       | 2.25<br>27        | 1.06<br>27        | C-D-E-F-G         |
| A12R126GV      | 12.00 x 12.00 x 6.00<br>305 x 305 x 152  | A          | —<br>—       | 2.25<br>27        | 1.06<br>27        | C-D-E-F-G         |
| A18R186GV      | 18.00 x 18.00 x 6.00<br>457 x 457 x 152  | B          | —<br>—       | 13.00<br>330      | 1.12<br>28        | A-B-C-D-E-F-G-H-I |
| A8R88GV        | 8.00 x 8.00 x 8.00<br>203 x 203 x 203    | A          | —<br>—       | 2.25<br>57        | 1.06<br>27        | F-G-H-I           |
| A8R88GVNK      | 8.00 x 8.00 x 8.00<br>203 x 203 x 203    | A          | —<br>—       | 2.25<br>57        | 1.06<br>27        | —                 |
| A10R108GVNK    | 10.00 x 10.00 x 8.00<br>254 x 254 x 203  | A          | —<br>—       | 2.25<br>57        | 1.06<br>27        | —                 |
| A12R128GV      | 12.00 x 12.00 x 8.00<br>305 x 305 x 203  | A          | —<br>—       | 2.25<br>57        | 1.06<br>27        | C-D-E-F-G         |
| A24R248GV      | 24.00 x 24.00 x 8.00<br>610 x 610 x 203  | C          | 12.19<br>310 | 13.00<br>330      | 1.12<br>28        | A-B-C-D-E-F-G-H-I |
| A24R2410GV     | 24.00 x 24.00 x 10.00<br>610 x 610 x 254 | C          | 12.19<br>310 | 13.00<br>330      | 1.12<br>28        | A-B-C-D-E-F-G-H-I |

