

Non-NEMA Twist-Lock® Devices  
30A, 125/250V AC, 3 Pole, 3 Wire  
Non-Grounding  
Insulgrip® Plug



Features

- Ribbed nylon housing provides a secure grip and impact and chemical resistance.
- Superior cord grip design protects terminations from excess strain.
- Clear, funnel shaped wire entry for ease of termination.
- Integral dust shield protects wiring chamber from dust or contaminants.

Ordering Information

|                        |                    |              |                |
|------------------------|--------------------|--------------|----------------|
| Description            | Cord Diameter      | UPC          | Catalog Number |
| Black and white nylon. | .360"-.930" (9-24) | 783585039817 | HBL3331C       |



Listings

|                              |
|------------------------------|
| Listed to UL 498             |
| Fed.Spec. W-C-596            |
| Certified to CSA C22.2 No.42 |

Specifications

|                      |                                               |
|----------------------|-----------------------------------------------|
| Housing / Cord Clamp | Nylon                                         |
| Terminal Retainer    | Clear polycarbonate                           |
| Blades               | Brass                                         |
| Terminal Screws      | #10-32 Brass (Phillips / Slotted / Robertson) |
| Terminal Clamp       | Cold rolled steel – nickel plated             |
| Assembly Screws      | Steel - nickel plated                         |

Accessories

|                   |           |
|-------------------|-----------|
| Connector         | HBL34333C |
| Single Receptacle | HBL3430   |
| Weatherproof Boot | HBL6031   |

Resources

|          |
|----------|
| eCatalog |
|----------|

Performance

|                         |                                                          |
|-------------------------|----------------------------------------------------------|
| <b>Electrical</b>       |                                                          |
| Current Interrupting    | Certified for current interrupting at full rated current |
| Dielectric Voltage      | Withstands 2,000V minimum                                |
| <b>Mechanical</b>       |                                                          |
| Terminal Accommodation  | #16 AWG - #8 AWG stranded copper wire only.              |
| Terminal Identification | Terminals identified in accordance with UL 498           |
| <b>Environmental</b>    |                                                          |
| Flammability            | HB or better per UL94/CSA 22.2 No.0.17                   |
| Moisture Resistance     | IP20 Suitability                                         |
| Operating Temperatures  | Maximum Continuous 75°C; Minimum -40°C (w/o impact)      |

