



Products at a Glance



HBL® Extra Heavy Duty Hospital Grade

- Deep nylon body design increases impact and chemical resistance
- One-piece nickel-plated brass ground strap
- ID marking surface for quick circuit identification
- Square head, 10-thread bronze center rivet
- External back wire clamp



HBL® Extra Heavy Duty

- One-piece brass ground strap
- Exclusive bypass contact design for greater contact force and reduced heat buildup
- Barbed assembly arms reduce possibility of face/base separation
- Deep face design



SNAPConnect® Extra Heavy Duty

- Hospital and Specification Grade
- SNAPConnect® modular wiring device system saves installation time
- Eliminates screw terminations
- Steel mounting strap, self-grounding
- Compact size requires minimal space
- Single receptacles available



Hubbell-PRO Heavy Duty

- Specification Grade and Hospital Grade
- Tamper-Resistant... **NOT** Plug Resistant™
- Power indicating LED feature optional
- Circuit ID marking area on Hospital Grade
- Steel mounting strap, self-grounding



USB Charger Receptacles

- Two Type-C, Type A&C and Type A port configurations, high power 5 Amp, 5 Volt DC USB output
- Heavy duty stainless steel USB ports; rated for 10,000 cord insertions and removals
- Patented Hubbell Tamper-Resistant technology uses cam action shutters; the friction-free design of the mechanism's doors requires much less force to open
- 4 Port and 2 Port outlet available



Commercial Specification Grade


- Installation ease
 - Single tab breakoff ears
 - Self-grounding staple
 - Easy access split circuit tab
- Tamper-Resistant... **NOT** Plug Resistant™
- Wrap-around galvanized steel straps




4-PLEX Receptacles

- Hospital Grade and Surge styles
- Mounts directly to 4-inch square box
- "A" and "B" circuit ID molded into face
- Removable knockouts for mounting to octagon concrete ring or box
- Heavy duty, triple wipe, brass power and ground contacts


15 and 20 Ampere, 125 Volts




8200LA




8200TRA



8200REDLTRA



2172LATRA



2182IVLTRA

Dimensions in Inches (mm)

Hubbell-PRO Heavy Duty Hospital Grade ● Receptacles

Duplex

Hospital grade,
smooth nylon face,
back and side wired.
Assembled in USA.

Color

Catalog Number

Black	8200BK	8300BK
Brown	8200	8300
Gray	8200GY	8300GY
Ivory	8200IV	8300IV
Light Almond	8200LA	8300LA
Red	8200RED	8300RED
White	8200WHI	8300WHI



Hospital grade, Tamper-Resistant,
smooth nylon face,
back and side wired.
Assembled in USA.

Black	8200BKTRA	8300BKTRA
Brown	8200TRA	8300TRA
Gray	8200GYTRA	8300GYTRA
Ivory	8200IVTRA	8300IVTRA
Light Almond	8200LATRA	8300LATRA
Red	8200REDTRA	8300REDTRA
White	8200WTRA	8300WTRA



Hospital grade,
with Power Indicating LED,
smooth nylon face,
back and side wired.
Assembled in USA.

Black	8200BKL	8300BKL
Brown	8200L	8300L
Gray	8200GYL	8300GYL
Ivory	8200IVL	8300IVL
Light Almond	8200LAL	8300LALM
Red	8200REDL	8300REDL
White	8200WL	8300WL



Hospital grade, Tamper-Resistant,
with Power Indicating LED,
smooth nylon face,
back and side wired.
Assembled in USA.



Black	8200BKLTRA	8300BKLTRA
Brown	8200LTRA	8300LTRA
Gray	8200GYLTRA	8300GYLTRA
Ivory	8200IVLTRA	8300IVLTRA
Light Almond	8200LALTRA	8300LALTRA
Red	8200REDLTRA	8300REDLTRA
White	8200WLTRA	8300WLTRA

Style Line® Decorator

Hospital grade,
Style Line® decorator,
flush, nylon face,
back and side wired.
Assembled in USA.

Black	2172BK	2182BK
Brown	2172	2182
Gray	2172GY	2182GY
Ivory	2172IV	2182IV
Light Almond	2172LA	2182LA
Red	2172RED	2182RED
White	2172W	2182W



Hospital grade, Tamper-Resistant,
Style Line® decorator,
flush, nylon face,
back and side wired.
Assembled in USA.

Black	2172BKTRA	2182BKTRA
Brown	2172TRA	2182TRA
Gray	2172GYTRA	2182GYTRA
Ivory	2172IVTRA	2182IVTRA
Light Almond	2172LATRA	2182LATRA
Red	2172REDTRA	2182REDTRA
White	2172WTRA	2182WTRA



Hospital grade,
with Power Indicating LED,
Style Line® decorator,
flush, nylon face,
back and side wired.
Assembled in USA.

Black	2172BKL	2182BKL
Brown	2172L	2182L
Gray	2172GYL	2182GYL
Ivory	2172IVL	2182IVL
Light Almond	2172LAL	2182LAL
Red	2172REDL	2182REDL
White	2172WL	2182WL



Hospital grade, Tamper-Resistant,
with Power Indicating LED,
Style Line® decorator,
flush, nylon face,
back and side wired.
Assembled in USA.

Black	2172BKLTRA	2182BKLTRA
Brown	2172LTRA	2182LTRA
Gray	2172GYLTRA	2182GYLTRA
Ivory	2172IVLTRA	2182IVLTRA
Light Almond	2172LALTRA	2182LALTRA
Red	2172REDLTRA	2182REDLTRA
White	2172WLTRA	2182WLTRA

Note: See pages A-47 and A-48 for accessories.

See page Tech-10 for Tamper-Resistant and LED Power Indicators descriptions.

See section N for wallplates.



Technical Information

Hubbell-PRO Heavy Duty, Straight Blade Hospital Grade Duplex Receptacles



Specifications

Receptacle	Part	Description
Typical Specification - Catalog No. 8200	Receptacle	15A
Manufacturer's Identification - Hubbell-PRO 8200	Top	Nylon
Description - Straight Blade Hospital Grade Duplex Receptacle	Base	Nylon
Type - 2 Pole, 3 Wire, Grounding	Triple Wipe Power Contacts	.0295 in. Brass
Rating - 15A, 125V	Clamping Plate	Plated Steel
Certification - UL Listed to UL 498, Fed. Spec. WC596	Mounting Strap	.040 in. Galvanized Steel
Hospital Grade, NEMA® WD-6 Compliant	Terminal Screws	Plated Steel
Certified to CSA	Hex Head Grounding Screw	Plated Steel
	Automatic Self-Grounding Staple	Stainless Steel
	Mounting Screws	Zinc Plated Steel

Performance

Electrical	
Dielectric Voltage	Withstands 2,000V minimum.
Max. Working Voltage	125V.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
Mechanical	
Terminal Identification	Terminals identified in accordance with UL 498 and CSA (Brass, White, Green)
Terminal Accommodation	#14-10 AWG stranded or solid copper conductor only.
Product Identification	Ratings are a permanent part of the device.
Environmental – Material	
Flammability	UL 94V-2.
Operating Temperature	Maximum continuous 75°C; minimum -40°C (w/o impact).

NEMA® is a registered trademark of the National Electrical Manufacturers Association.