

HBL9430A

30A, 125/250V, 3 Pole, 4 Wire Grounding, Receptacles and Plugs

IP20
SUITABILITY




**30A 125/250V
NEMA 14-30R
2(2) HP**



**30A 125/250V
NEMA 14-30P
2(2) HP**

Description	Cord Diameter	Catalog Number
Receptacle, black RTP.	—	HBL9430A
Plug, nylon.	.625"-1.310" (15.9-33.3)	HBL9431C
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	HBL9432C



HBL9431C

30A, 3Ø 250V AC, 3 Pole, 4 Wire Grounding, Receptacles and Plugs

IP20
SUITABILITY




**30A 3Ø 250V AC
NEMA 15-30R
3 HP**




**30A 3Ø 250V AC
NEMA 15-30P
3 HP**

Description	Cord Diameter	Catalog Number
Receptacle, black RTP.	—	HBL8430A
Plug, nylon.	.625"-1.310" (15.9-33.3)	HBL8431C
Plug, nylon, angle, 4-position	.625"-1.310" (15.9-33.3)	HBL8432C



HBL9432C



HBL8330A



30A, 3ØY 120/208V AC, 4 Pole, 4 Wire Non-Grounding, Receptacles and Plugs

IP20
SUITABILITY




**30A 3ØY
120/208V AC
NEMA 18-30R
UL Listed
3 HP**



**30A 3ØY
120/208V AC
NEMA 18-30P
UL Listed
3 HP**

Description	Cord Diameter	Catalog Number
Receptacle, black RTP.	—	HBL8330A
Plug, nylon.	.625"-1.310" (15.9-33.3)	HBL8331C

*Note: RTP is an abbreviation for reinforced thermoplastic polyester.
See pages A-49 and A-50 for accessories.*



HBL8331C

Dimensions in Inches (mm)