


**30 Amp, 125, 250 Volts and 277 Volts AC
2 Pole, 3 Wire, Grounding**




HBL2611SW



HBL2621S




HBL2621



HBL2611VY



HBL2615SW



HBL2625

Dimensions in Inches (mm)

Plugs

Watertight Safety-Shroud®

Description	Cord Dia.	Catalog Number	IP66 SUITABILITY	UL Type 4x, 12
Black Valox® housing, white Valox® clamps.	.325"-.930" (9-24)	HBL2611SW	HBL2621SW	—

Safety-Shroud®

Description	Cord Dia.	Catalog Number	IP20 SUITABILITY
Black and white nylon body, white Valox® shroud. Can be used with the Insulgrip Connector Bodies.	.360"-.930" (9-24)	HBL2611S	HBL2621S

Note: See page B-40 for accessories.

Insulgrip®

Description	Cord Dia.	Catalog Number	IP20 SUITABILITY
Black and white nylon.	.360"-.930" (9-24)	HBL2611	HBL2621
Heat stabilized, gray nylon, 220° F (104° C).	.360"-.930" (9-24)	HBL2611F	HBL2621F
Corrosion resistant, yellow nylon.	.360"-.930" (9-24)	HBL26CM11	HBL26CM21
All black nylon.	.360"-.930" (9-24)	HBL2611BK	HBL2621BK
Cord clamps with removable inserts. All black nylon.	.360"-.930" (9-24)	—	HBL2621EBK

Note: See page B-52 for accessories.

Valise®

Description	Cord Dia.	Catalog Number	IP20 SUITABILITY
Yellow nylon.	.590"-.930" (15.0-23.6)	HBL2611VY	HBL2621VY
Corrosion resistant, yellow nylon.	.590"-.930" (15.0-23.6)	HBL26CM11V	—
Black nylon.	.590"-.930" (15.0-23.6)	HBL2611VBK	HBL2621VBK

Note: See page B-53 for accessories.

Flanged Inlets

Watertight Safety-Shroud®

Description	Catalog Number	IP66 SUITABILITY	UL Type 4x, 12
Gray Valox® housing and flange.	HBL2615SW	HBL2625SW	—
Reverse service, gray Valox® housing and flange (use with HBL2613SR), (Not shown).	HBL2615SWR	—	—

Note: See page B-54 for accessories.

Insulgrip®

Description	Catalog Number	IP20 SUITABILITY
Nylon casing, back wired.	HBL2615	HBL2625
Heat stabilized, gray nylon, 220° F (104° C).	HBL2615F	HBL2625F
Nylon casing, weather protective, die cast aluminum, back wired, self closing lift cover.	HBL2615M3	—

Note: See page B-52 for accessories.

See pages B-69 and B-70 for technical information on Twist-Lock and Watertight Safety-Shroud devices.
See page B-74 for technical information on Valise plugs and connectors.

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.