



## Features and Benefits

### 50 Amp Plugs and Connector Bodies

Hubbell's 50 amp Twist-Lock® devices feature a heavy duty design built for heavy duty applications. These Hubbell 50 amp Twist-Lock plugs and connector bodies are built to go where you need power, even in some of the harshest environments.

On the outside, 50 amp plugs and connectors are made of super tough nylon for better impact resistance. On the plug, the stainless steel shroud not only provides protection and durability, but safety as well. That's because the rigid construction restricts distortion, thus minimizing the possibility of mating incorrect devices.

On the inside are the kinds of features that separate Hubbell from all the rest. The cord grip has been designed with offset gripping jaws to securely hold the conductors – not just the cord jacket. Hubbell's box terminals speed wiring and provide a superior termination. The plug's thermoplastic polyester interior provides excellent heat resistance without compromising strength.

In all, it's the combination of function and performance that Hubbell demands of all its products. That is why we will never add a feature that compromises performance.



CS6361C




CS6360C



#### Housing Design

- Housing assembly latch slotted to fit standard flat-blade screwdriver providing secure assembly and fast disassembly for wiring
- Super tough nylon housing offers better impact qualities




#### Internal Design

- Thermoplastic polyester interior provides heat resistance and impact strength
- 6/6 nylon nose – thermoplastic polyester terminal cover provides heat resistance in terminal area and impact strength of nose piece



#### Safety

- Stainless steel shroud restricts mismating with the wrong device
- Padlock capable shroud allows compliance to OSHA lockout tagout regulation 29 CFR 1910.147



#### Terminals

- Box terminal with hex socket threaded slug is superior because it permits high clamping pressure on conductors without damaging strands



#### Installation

- Three-piece thermoplastic cord clamp assembly with stainless steel fast lead screws provides a more consistent, durable grip. Sealed cable entry keeps out moisture and dust



#### Contacts

- One-piece grounding contact on 4-wire devices provides a more reliable grounding system for a safer device

## 50 Amp, 125, 250 Volts and 480 Volts AC




**IP20**  
SUITABILITY



### Plugs

| Description                                      | Cord Dia.                     | Catalog Number |                |                |
|--------------------------------------------------|-------------------------------|----------------|----------------|----------------|
| Nylon housing, thermoplastic polyester interior. | .830"-1.250"<br>(21.08-31.75) | <b>CS6361C</b> | <b>CS8265C</b> | <b>CS8465C</b> |

Note: See page B-60 for accessories.



### Flanged Inlets

| Description                                   | Catalog Number |               |                |
|-----------------------------------------------|----------------|---------------|----------------|
| Zinc plated steel casing, thermoset interior. | <b>CS6377†</b> | <b>CS8275</b> | <b>CS8475†</b> |




**IP20**  
SUITABILITY



### Connector Bodies

| Description                                      | Cord Dia.                     | Catalog Number |                |                |
|--------------------------------------------------|-------------------------------|----------------|----------------|----------------|
| Nylon housing, thermoplastic polyester interior. | .830"-1.250"<br>(21.08-31.75) | <b>CS6360C</b> | <b>CS8264C</b> | <b>CS8464C</b> |

Note: See page B-60 for accessories.



### Receptacles

| Description     | Catalog Number |               |                |
|-----------------|----------------|---------------|----------------|
| Black phenolic. | <b>CS6370</b>  | <b>CS8269</b> | <b>CS8469†</b> |

Note: See page B-60 for accessories.  
†Not CSA Certified.

Dimensions in Inches (mm)