

USB Charger Receptacles and Outlets



Weather Resistant Receptacle Features

- Meets Section 406.9 of NEC®
- 5 Amp, 5 Volt USB output
- Type A&C USB ports
- Power indicating green LED light



Weather Resistant USB Charger Duplex Receptacles

Description	Color	15A 125V	20A 125V
Type A&C USB Charger Receptacle, One Type A and one Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant USB ports rated 10,000 cycles; Commercial Grade	Black	USB15AC5BKWR	USB20AC5BKWR
	Brown	USB15AC5WR	USB20AC5WR
	Gray	USB15AC5GYWR	USB20AC5GYWR
	Ivory	USB15AC5IWR	USB20AC5IWR
	Light Almond	USB15AC5LAWR	USB20AC5LAWR
	White	USB15AC5WWR	USB20AC5WWR


Note: Outdoor circuits should be GFCI protected per national and local electric codes.

Commercial & Hospital Grade USB Charger Tamper-Resistant Duplex Receptacles




Description	Color	Commercial		Hospital Grade	
		15A 125V	20A 125V	15A 125V	20A 125V
Two Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant duplex receptacle, USB ports rated 10,000 cycles.	Black	USB15C5BK	USB20C5BK	USB8200C5BK	USB8300C5BK
	Brown	USB15C5	USB20C5	USB8200C5	USB8300C5
	Gray	USB15C5GY	USB20C5GY	USB8200C5GY	USB8300C5GY
	Ivory	USB15C5I	USB20C5I	USB8200C5I	USB8300C5I
	Lt. Almond	USB15C5LA	USB20C5LA	USB8200C5LA	USB8300C5LA
	Red	—	—	USB8200C5R	USB8300C5R
One Type A and one Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant duplex receptacle, USB ports rated 10,000 cycles.	White	USB15C5W	USB20C5W	USB8200C5W	USB8300C5W
	Black	USB15AC5BK	USB20AC5BK	USB8200AC5BK	USB8300AC5BK
	Brown	USB15AC5	USB20AC5	USB8200AC5	USB8300AC5
	Gray	USB15AC5GY	USB20AC5GY	USB8200AC5GY	USB8300AC5GY
	Ivory	USB15AC5I	USB20AC5I	USB8200AC5I	USB8300AC5I
	Lt. Almond	USB15AC5LA	USB20AC5LA	USB8200AC5LA	USB8300AC5LA
Two Type A port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant duplex receptacle, USB ports rated 10,000 cycles.	Red	—	—	USB8200AC5R	USB8300AC5R
	White	USB15AC5W	USB20AC5W	USB8200AC5W	USB8300AC5W
	Black	USB15A5BK	USB20A5BK	USB8200A5BK	USB8300A5BK
	Brown	USB15A5	USB20A5	USB8200A5	USB8300A5
	Gray	USB15A5GY	USB20A5GY	USB8200A5GY	USB8300A5GY
	Ivory	USB15A5I	USB20A5I	USB8200A5I	USB8300A5I
	Lt. Almond	USB15A5LA	USB20A5LA	USB8200A5LA	USB8300A5LA
	Red	—	—	USB8200A5R	USB8300A5R
	White	USB15A5W	USB20A5W	USB8200A5W	USB8300A5W

Note: See page Tech-10 for Tamper-Resistant description. See section L for Hospital grade series.



USB8300C5W




USB15AC5GY

4 Port USB Charger Outlets



Description	Color	4 Type A ports	2 Type A and 2 Type-C ports	4 Type-C ports
USB Charger Outlets, 4 USB ports, 5 Amp, 5 Volt DC, Style Line® decorator.	Black	USB4BK	USB4ACBK	USB4CBK
	Brown	USB4	USB4AC	USB4C
	Gray	USB4GY	USB4ACGY	USB4CGY
	Ivory	USB4I	USB4ACI	USB4CI
	Light Almond	USB4LA	USB4ACLA	USB4CLA
	White	USB4W	USB4ACW	USB4CW



USB4W

Switch Combo Outlets



Description	Color	Catalog Number
Switch Combo Outlet, two USB type 2.0 ports, 2.1 Amp, 5 Volt DC, Style Line® decorator.	Black	USB102BK
	Brown	USB102
	Gray	USB102GY
	Ivory	USB102I
	Light Almond	USB102LA
	White	USB102W



USB102W

Dimensions in Inches (mm)

NEC® is a registered trademark of the National Fire Protection Association (NFPA).

Features and Benefits

Power Charging Pedestals

Hubbell's On-the-Go Power Charging pedestals ships ready to install with four 20A 125V tamper-resistant USB Type A and Type C combination duplex receptacles, with a ¾ inch NPT hub in the base and 36 inch long wire leads the assembly will accommodate all installations when fed from the floor below. The pedestal can also be mounted and wired over one of Hubbell's flush round floor boxes or single gang rectangular floor boxes.

Our 2 inch by 8 inch wing-shaped aluminum extrusion has a sturdy ¼ inch thick aluminum base plate with four pre-drilled counter sunk holes for mounting. Because of its shallow design, the pedestals can be mounted between most back-to-back transportation seating arrangements.

HUBBELL ON-the-GO CHARGING

Power Charging Pedestals



(Front View)



(Side View)



Housing Design

- Durable powder coated aluminum extrusion offers a permanent solution for high traffic areas
- Ships ready to install



Power Stands

- Back to back 39.79 inch and 34.29 inch receptacle heights will clear backs of transportation seating chairs



Charging Power

- Duplex receptacles include Hubbell's patented tamper-resistant technology allowing the plug to slide in effortlessly
- Combination Type A and Type-C USB configuration meets most charging needs



Installation

- Integral ¾ inch conduit hub in base
- Single circuit pre-wired assembly with 36 inch long #12 AWG wire leads
- Sleek 2 inch by 8 inch powder coated aluminum extrusion design at 52.40 inches tall



USB Ports

- Heavy-duty stainless steel USB ports are rated for 10,000 cord insertions and removals



Custom Branding

- Custom branding/graphics available for light kit
- Available with energy efficient LED light kit to add visibility
- Indoor use only

Description	Color	Catalog Number
Hubbell Charging Power Stand, 52.40 inches tall.	Gray	HCPWRPED52GRY
Hubbell Charging Power Stands, 52.40 inches tall, Light Kit.	Gray	HCPWRPED52LKGRY

Description	Color	Catalog Number
Hubbell Charging Power Stands, 52.40 inches tall, Light Kit with Custom Branding.	Gray	HCPWRPED52LKGRYxxx
Custom Artwork Specification.	Maximum print area: 6.75" W x 9.13" H Preferred file formats: Adobe Illustrator, Vector File, Encapsulated Postscript and Layered PDF	

[illegible]

R-7



USB Charging Receptacles Type-C • Type A&C • Type A

Hubbell USB Chargers are available in the new Type-C port, a combination unit with Type A&C, and the legacy Type A. All with the increase in power to a 5 Amp 5 Volt USB port adds capacity so that there is always ample current to support multiple device charging. Portable mobile manufacturers are using the faster Type-C ports. More phones, tablets and other electronic devices are expected to use this new standard.

- Compliant with USB BC1.2 battery charging and 3.0 power delivery.
Compatible with USB 2.0, 3.0 and 3.1 devices
- USB Type-C port is legacy USB Type A compatible (adapter cord - not included)
- Heavy duty stainless steel USB ports; rated for 10,000 cord insertions and removals
- Patented Hubbell Tamper-Resistant technology uses cam action shutters
- Designed for commercial, industrial and home use
- Weather resistant receptacles Meets Section 406.9 of NEC®
- Weather resistant receptacles available in Type A&C USB ports only



Weather Resistant USB Charger Duplex Receptacles

Description	Color	15A 125V	20A 125V
Type A&C USB Charger Receptacle, One Type A and one Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant Commercial Grade USB ports rated 10,000 cycles.	Black Brown Gray Ivory Light Almond White	USB15AC5BKWR USB15AC5WR USB15AC5GYWR USB15AC5IWR USB15AC5LAWR USB15AC5WWR	USB20AC5BKWR USB20AC5WR USB20AC5GYWR USB20AC5IWR USB20AC5LAWR USB20AC5WWR


Note: Outdoor circuits should be GFCI protected per national and local electric codes.

USB Charger Duplex Receptacles Type-C, Type A&C and Type A


Description	Color	15A 125V	20A 125V
Hospital Grade USB Charger Receptacle, two Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant duplex receptacle, USB ports rated 10,000 cycles.	Black Brown Gray Ivory Light Almond Red White	USB8200C5BK USB8200C5 USB8200C5GY USB8200C5I USB8200C5LA USB8200C5R USB8200C5W	USB8300C5BK USB8300C5 USB8300C5GY USB8300C5I USB8300C5LA USB8300C5R USB8300C5W
Hospital Grade USB Charger Receptacle, one Type A and one Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant duplex receptacle, USB ports rated 10,000 cycles.	Black Brown Gray Ivory Light Almond Red White	USB8200AC5BK USB8200AC5 USB8200AC5GY USB8200AC5I USB8200AC5LA USB8200AC5R USB8200AC5W	USB8300AC5BK USB8300AC5 USB8300AC5GY USB8300AC5I USB8300AC5LA USB8300AC5R USB8300AC5W
Hospital Grade USB Charger Receptacle, two Type A port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant duplex receptacle, USB ports rated 10,000 cycles.	Black Brown Gray Ivory Light Almond Red White	USB8200A5BK USB8200A5 USB8200A5GY USB8200A5I USB8200A5LA USB8200A5R USB8200A5W	USB8300A5BK USB8300A5 USB8300A5GY USB8300A5I USB8300A5LA USB8300A5R USB8300A5W
Commercial Grade USB Charger Receptacle, two Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant duplex receptacle, USB ports rated 10,000 cycles.	Black Brown Gray Ivory Light Almond White	USB15C5BK USB15C5 USB15C5GY USB15C5I USB15C5LA USB15C5W	USB20C5BK USB20C5 USB20C5GY USB20C5I USB20C5LA USB20C5W
Commercial Grade USB Charger Receptacle, one Type A and one Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant duplex receptacle, USB ports rated 10,000 cycles.	Black Brown Gray Ivory Light Almond White	USB15AC5BK USB15AC5 USB15AC5GY USB15AC5I USB15AC5LA USB15AC5W	USB20AC5BK USB20AC5 USB20AC5GY USB20AC5I USB20AC5LA USB20AC5W
Commercial Grade USB Charger Receptacle, two Type A port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant duplex receptacle, USB ports rated 10,000 cycles.	Black Brown Gray Ivory Light Almond White	USB15A5BK USB15A5 USB15A5GY USB15A5I USB15A5LA USB15A5W	USB20A5BK USB20A5 USB20A5GY USB20A5I USB20A5LA USB20A5W

Note: See page Tech-10 for Tamper-Resistant description. See section N for wallplates.


NEC® is a registered trademark of the National Fire Protection Association (NFPA).




USB15AC5WWR



USB8300C5W



USB15AC5GY



USB20A5I

Dimensions in Inches (mm)

USB Charger Receptacles and Outlets



Weather Resistant Receptacle Features

- Meets Section 406.9 of NEC®
- 5 Amp, 5 Volt USB output
- Type A&C USB ports
- Power indicating green LED light



Weather Resistant USB Charger Duplex Receptacles

Description	Color	15A 125V	20A 125V
Type A&C USB Charger Receptacle, One Type A and one Type-C port configurations, high power 5 Amp, 5 Volt USB output, Tamper-Resistant USB ports rated 10,000 cycles; Commercial Grade	Black	USB15AC5BKWR	USB20AC5BKWR
	Brown	USB15AC5WR	USB20AC5WR
	Gray	USB15AC5GYWR	USB20AC5GYWR
	Ivory	USB15AC5IWR	USB20AC5IWR
	Light Almond	USB15AC5LAWR	USB20AC5LAWR
	White	USB15AC5WWR	USB20AC5WWR

Note: Outdoor circuits should be GFCI protected per national and local electric codes.



USB15AC5WWR



Standard USB Charger Tamper-Resistant Duplex Receptacles

Description	Color	15A 125V	20A 125V
Type-C USB Charger Receptacle, two Type-C port configurations, high power 5 Amp, 5 Volt USB output.	Black	USB15C5BK	USB20C5BK
	Brown	USB15C5	USB20C5
	Gray	USB15C5GY	USB20C5GY
	Ivory	USB15C5I	USB20C5I
	Light Almond	USB15C5LA	USB20C5LA
	White	USB15C5W	USB20C5W
Type A&C USB Charger Receptacle, one Type A and one Type-C port configuration, high power 5 Amp, 5 Volt USB output.	Black	USB15AC5BK	USB20AC5BK
	Brown	USB15AC5	USB20AC5
	Gray	USB15AC5GY	USB20AC5GY
	Ivory	USB15AC5I	USB20AC5I
	Light Almond	USB15AC5LA	USB20AC5LA
	White	USB15AC5W	USB20AC5W
Type A USB Charger Receptacle, two Type A port configurations, high power 5 Amp, 5 Volt USB output.	Black	USB15A5BK	USB20A5BK
	Brown	USB15A5	USB20A5
	Gray	USB15A5GY	USB20A5GY
	Ivory	USB15A5I	USB20A5I
	Light Almond	USB15A5LA	USB20A5LA
	White	USB15A5W	USB20A5W

Note: See page Tech-10 for Tamper-Resistant description.
See section L for Hospital grade series.



USB15C5W



USB15AC5W

4 Port USB Charger Outlets

Description	Color	4 Type A ports	2 Type A and 2 Type-C ports	4 Type-C ports
USB Charger Outlets, 4 USB ports, 5 Amp, 5 Volt DC, Style Line® decorator.	Black	USB4BK	USB4ACBK	USB4CBK
	Brown	USB4	USB4AC	USB4C
	Gray	USB4GY	USB4ACGY	USB4CGY
	Ivory	USB4I	USB4ACI	USB4CI
	Light Almond	USB4LA	USB4ACLA	USB4CLA
	White	USB4W	USB4ACW	USB4CW



USB20A5W

Switch Combo Outlets

Description	Color	Catalog Number
Switch Combo Outlet, two USB type 2.0 ports, 2.1 Amp, 5 Volt DC, Style Line® decorator	Black	USB102BK
	Brown	USB102
	Gray	USB102GY
	Ivory	USB102I
	Light Almond	USB102LA
	White	USB102W



USB102W



USB4ACW

NEC® is a registered trademark of the National Fire Protection Association (NFPA).