

Catalog Number:	CTPA08-S/OR/100M
Product ID:	7TCA298000R0025
EAN Number:	05020963797378
Status:	Active

Lightweight Weight, Extra Flexible Slit Conduit, NC Size 08/NW Size 7.5, Outside Diameter 10.0mm, Inside Diameter 6.5mm, Static Bend Radius 10mm, High Fatigue Life and Abrasion, Impact Resistance, IP40 Rating, Polyamide 6, Reel Length 100 Meters, Orange

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5540 Flexible Non-Metallic Conduit
Brand Name	Harnessflex
Type	Slit Lightweight Conduit
Special Features	Self Extinguishing, Low Smoke Toxicity & Halogen Free
Application	General Purpose, Lightweight Loom Applications
Standard	RoHS, Conforms with End of Life Vehicle Directive (ELV)EU200/53/EC
Trade Size	NC08/NW7.5
Outside Diameter	10.0mm
Inside Diameter	6.5mm
Length	100 m
Radius	Static Bend Radius 10mm
Flexibility	High
Material	Polyamide/Nylon 6
Color	Orange

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	8mm
Nominal size in inch	1/8 inch
Outer diameter	10mm
Inner diameter	6.5mm
Material	Polyamide 6
Operating temperature	-40-+120°C
Degree of protection (IP)	IP40
Fire resistance in accordance with UL94	HB
UV resistant	Y
Colour	Orange
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	Y
Halogen free	Y

Packaging

Outer Quantity	15
Outer Dimensions (inches)	1x1x1
Weight Uom	1 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289

