

Catalog Number: CTPA32-S/50M
Product ID: 7TCA298000R0121
EAN Number: 05020963022678
Status: Active

Lightweight Weight, Extra Flexible Slit Conduit, NC Size 32/NW Size 29, Outside Diameter 34.5mm, Inside Diameter 28.8mm, Static Bend Radius 55mm, High Fatigue Life and Abrasion, Impact Resistance, IP40 Rating, Polyamide 6, Reel Length 50 Meters, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5540 Flexible Non-Metallic Conduit
Brand Name	Harnessflex
Type	Slit Lightweight Conduit
Special Features	Self Extinguishing, Low Smoke Toxicity & Halogen Free
Application	General Purpose, Lightweight Loom Applications
Standard	RoHS, Conforms with End of Life Vehicle Directive (ELV)EU200/53/EC
Trade Size	NC32/NW29
Outside Diameter	34.5mm
Inside Diameter	28.8mm
Length	50 m
Radius	Static Bend Radius 55mm
Flexibility	High
Material	Polyamide/Nylon 6
Color	Black

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	32mm
Nominal size in inch	1 inch
Outer diameter	34.5mm
Inner diameter	28.8mm
Material	Polyamide 6
Operating temperature	-40-+120°C
Degree of protection (IP)	IP40
Fire resistance in accordance with UL94	HB
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	Y
Halogen free	Y

Packaging

Inner Quantity	1
Inner Dimensions (inches)	24.5x24.5x50
Outer Quantity	1
Outer Dimensions (inches)	48x40x50
Weight Uom	9.37 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321

