


**30 Amp, 125, 250 Volts and 277 Volts AC
2 Pole, 3 Wire, Grounding**




HBL2611SW



HBL2621S




HBL2621



HBL2611VY



HBL2615SW



HBL2625

Dimensions in Inches (mm)



**30A 125V
NEMA L5-30P
2 HP**



**30A 250V
NEMA L6-30P
2 HP**



**30A 277V AC
NEMA L7-30P
3 HP**

Plugs

Watertight Safety-Shroud®

IP66 SUITABILITY

UL Type 4x, 12

Description	Cord Dia.	Catalog Number
Black Valox® housing, white Valox® clamps.	.325"-.930" (9-24)	HBL2611SW HBL2621SW -

Safety-Shroud®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number
Black and white nylon body, white Valox® shroud. Can be used with the Insulgrip Connector Bodies.	.360"-.930" (9-24)	HBL2611S HBL2621S -

Note: See page B-42 for accessories.

Insulgrip®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number
Black and white nylon.	.360"-.930" (9-24)	HBL2611 HBL2621 HBL2631
Heat stabilized, gray nylon, 220° F (104° C).	.360"-.930" (9-24)	HBL2611F HBL2621F -
Corrosion resistant, yellow nylon.	.360"-.930" (9-24)	HBL26CM11 HBL26CM21 -
All black nylon.	.360"-.930" (9-24)	HBL2611BK HBL2621BK -
Cord clamps with removable inserts. All black nylon.	.360"-.930" (9-24)	- HBL2621EBK -

Note: See page B-54 for accessories.

Valise®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number
Yellow nylon.	.590"-.930" (15.0-23.6)	HBL2611VY HBL2621VY -
Corrosion resistant, yellow nylon.	.590"-.930" (15.0-23.6)	HBL26CM11V - -
Black nylon.	.590"-.930" (15.0-23.6)	HBL2611VBK HBL2621VBK -

Note: See page B-55 for accessories.

Flanged Inlets

Watertight Safety-Shroud®

IP66 SUITABILITY

UL Type 4x, 12

Description	Catalog Number
Gray Valox® housing and flange.	HBL2615SW HBL2625SW -
Reverse service, gray Valox® housing and flange (use with HBL2613SR), (Not shown).	HBL2615SWR - -

Note: See page B-56 for accessories.

Insulgrip®

IP20 SUITABILITY

Description	Catalog Number
Nylon casing, back wired.	HBL2615 HBL2625 HBL2635
Heat stabilized, gray nylon, 220° F (104° C).	HBL2615F HBL2625F -
Nylon casing, weather protective, die cast aluminum, back wired, self closing lift cover.	HBL2615M3 - -

Note: See page B-54 for accessories.

See pages B-71 and B-72 for technical information on Twist-Lock and Watertight Safety-Shroud devices.

See page B-76 for technical information on Valise plugs and connectors.

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.