

**30 Amp, 3ØY 120/208, 277/480 and 347/600 Volts AC
4 Pole, 4 Wire, Non-Grounding**

IP20
SUITABILITY



30A 3ØY 120/208V AC
NEMA L18-30P
3 HP

30A 3ØY 277/480V AC
NEMA L19-30P
10 HP

30A 3ØY 347/600V AC
NEMA L20-30P

Plugs

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	HBL2751	HBL2761	HBL2771

Note: See page B-55 for accessories.

Flanged Inlets

Description	Catalog Number		
Nylon casing, back wired.	HBL2755	HBL2765	HBL2775

Note: See page B-54 for accessories.

IP20
SUITABILITY



30A 3ØY 120/208V AC
NEMA L18-30R
3 HP

30A 3ØY 277/480V AC
NEMA L19-30R
10 HP

30A 3ØY 347/600V AC
NEMA L20-30R

Connector Bodies

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	HBL2753	HBL2763	HBL2773

Note: See page B-54 for accessories.

Single Flush Receptacles

Description	Catalog Number		
Black nylon face, back and side wired.	HBL2750	HBL2760	HBL2770

Note: See page B-54 for accessories.

Flanged Receptacles


Description	Catalog Number		
Nylon casing, back wired.	HBL2756	HBL2766	HBL2776

Note: See page B-54 for accessories.

See page B-71 for technical information on Twist-Lock devices.




HBL2751




HBL2755



HBL2753



HBL2750



HBL2756

Dimensions in Inches (mm)