



Powering Business Worldwide

pe.eaton.com

Class 1 Division 2 Groups C and D, Hazardous Location Transformer

Z48D29T09CUS6

UPC:786680099694

Dimensions:

- **Height:** 15.94 IN
- **Length:** 10 IN
- **Width:** 21.37 IN

Weight:234 LB

Notes:Grade 316 stainless steel enclosure

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Class 1 Division 2 Groups C and D, Hazardous Location Transformer
- **Design:** EPTZ
- **Coil Material:** Copper windings
- **Enclosure:** NEMA 3R
- **Frame:** 103H
- **Frequency Rating:** 60 Hz
- **Phase:** Three-phase
- **Primary Voltage:** 480V
- **Secondary Voltage:** 208V
- **Tap Size:** 2 at +2.5% FCAN, 2 at -2.5% FCBN
- **Temperature Rating:** 115°C
- **Volt Ampere Rating:** 9 KVA
- **Weathershield:** Indoor-Outdoor
- **Wiring Connection:** 232A

Supporting documents:

- [Eatons Volume 2-Commercial Distribution](#)



- [Eaton Specification Sheet - Z48D29T09CUS6](#)

Certifications:

- UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.