

**P&C Flex Corrugated Flexible Conduit**
T&B Catalog Number:**UPC Number:**

11811D-2500

Status:

03448118648

Description:

Active

2 inch P&C Flex Detectable tape, length - 2500 ft.

Features

Accommodates any degree of bend, ideal for shallow trenches.

Easily handles offsets.

Manufactured to IPS dimensions, can be used with standard IPS couplings and fittings.

UV Resistant

Can be used as a flexible sweep or raceway, one SKU can do multiple bends.

General

Material

Non-Metallic

Reel Length (feet)

2500

Dimension Information

I.D. (inches)

2.045

Size (inches)

2

O.D. (inches)

2.375

Packaging

T&B Order Multiple

2500

Package in Units

2500

T&B Sold in UOM

Feet

T&B Weight Per UOM

0.34 lbs. Each

Application Support

Product Overview-P&C Flex

Available on Website

Notes

NOT UL Listed

Certifications

RoHS Compliance

Yes

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com