

3-pin female collector, type 1 3-pin connector, female IPCs Further information, Quantity and content: see technical data



General information	
Product type designation	Power supply unit connector
Control elements	
Frame size/design	
• Standard	Yes; Z shape
Installation type/mounting	
Wall mounting/direct mounting	Yes; can be plugged into SIMATIC HMI device
Supply voltage	
Rated value (DC)	24 V; DC
Interfaces	
HMI-side interface	
• Number of pins HMI-side	3; Male
Device-side interface	
• Number of pins device-side	3; Female, screw terminals
Standards, approvals, certificates	
Use in hazardous areas	
• ATEX Zone 2	Yes; Device-dependent, see operating instructions

- ATEX Zone 22
- IECEx Zone 2
- IECEx Zone 22
- cULus Class I Zone 1
- cULus Class I Zone 2, Division 2
- FM Class I Division 2

Yes; Device-dependent, see operating instructions
 Yes; Device-dependent, see operating instructions
 Yes; Device-dependent, see operating instructions
 Yes; Device-dependent, see operating instructions
 Yes; Device-dependent, see operating instructions
 Yes; Device-dependent, see operating instructions

Ambient conditions

Ambient temperature during operation

- min. 0 °C
- max. 55 °C

Ambient temperature during storage/transportation

- min. -20 °C
- max. 70 °C

Relative humidity

- Operation, max. 95 %

Mechanics/material

Material

- Plastic Yes; Green

Screw type

- 4.5 V Yes; Screw terminals

Dimensions

Width	15.5 mm
Height	27 mm
Thickness	15 mm

Scope of supply

Delivery quantity in pieces	5
-----------------------------	---

Other

Merchandise	Yes
Manufacturer name	SIEMENS AG
Manufacturer's address	Gleiwitzerstraße 555, 90475 Nuremberg, Germany
Target devices	For IPC and thin client with corresponding interface

last modified: 03/17/2020