

SCALANCE XP216EEC, managed IE switch, with railway approval (EN 50155, EN 45545); 12x 10/100 Mbps M12 ports, 4x 10/100/1000 Mbps M12 ports IP65, LED diagnostics, error signaling contact, Redundant power supply, PROFINET IO device, network management, operable in redundant ring, incl. dust caps, incl. electronic Manual on CD-ROM, C-plug optional



Product type designation	SCALANCE XP216EEC
Transmission rate	
Transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
Interfaces / for communication / integrated	
Number of electrical connections	
• for network components or terminal equipment	16
Number of 10/100 Mbit/s M12-ports (D-coded) / Integrated	12
Number of 10/100/1000 Mbit/s M12-ports (X-coded) / Integrated	4
Interfaces / others	
Number of electrical connections	
• for operator console	1
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for operator console	5 pin M12 socket (A coded)

• for signaling contact • for power supply	5-pin M12 connector (B-coded) 4-pin M12 plug (A-coded)
design of the removable storage	
• C-PLUG	Yes

Signal-Inputs/outputs

Operating voltage / of the signaling contacts	
• at DC / Rated value	24 V
Operating current / of the signaling contacts	
• at DC / maximum	0.1 A

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	
• external	24 V
• external / minimum	19.2 V
• external / maximum	28.8 V
Supply voltage / 1 / Rated value	XP-200EEC with EN 50155 supports the voltage range 16.8 ... 30 V DC
• Consumed current / 1 / at rated supply voltage / maximum	0.4 A
• Power loss [W] / 1 / Rated value	9.6 W
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	5 A / 60 V
Consumed current / maximum	0.335 A
Power loss [W]	
• at DC / at 24 V	8 W

Permitted ambient conditions

Ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
• Note	EEC variants with EN 50155 support for 10 minutes: -40 °C ... +85 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP65

Design, dimensions and weight

Design	compact
Width	280 mm
Height	200 mm
Depth	49 mm

Net weight	2.5 kg
Product feature / conformal coating	Yes
Material / of the enclosure	Aluminum
Mounting type	ET200pro module carrier
• wall mounting	Yes

Product properties, functions, components / general

Cascading in the case of a redundant ring / at reconfiguration time of <~0.3~s	50
Cascading in cases of star topology	any (depending only on signal propagation time)

Product functions / management, configuration

Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	Yes
• RMON	Yes
• Port mirroring	Yes
• multiport mirroring	Yes
• CoS	Yes
• with IRT / PROFINET IO switch	No
• PROFINET IO diagnosis	Yes
PROFINET conformity class	B
Product function / switch-managed	Yes
Telegram length / for Ethernet / maximum	1518 byte
Protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	No
• DCP	Yes
• LLDP	Yes
• EtherNet/IP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
Identification & maintenance function	
• I&M0 - device-specific information	Yes

- I&M1 – higher-level designation/location designation

Yes

Product functions / Diagnosis

Product function

- Port diagnostics
- Statistics Packet Size
- Statistics packet type
- Error statistics
- SysLog
- loopback diagnostics

Yes

Yes

Yes

Yes

Yes

Yes

Product functions / VLAN

Product function

- VLAN - port based
- VLAN - protocol-based
- VLAN - IP-based
- VLAN dynamic

Yes

No

No

No

Number of VLANs / maximum

4094

Product functions / DHCP

Product function

- DHCP server
- DHCP client
- DHCP Option 82
- DHCP Option 66
- DHCP Option 67

Yes

Yes

Yes

Yes

Yes

Product functions / Redundancy

Product function

- of the PROFINET IO device / is supported / PROFINET system redundancy (S2)
- Ring redundancy
- High Speed Redundancy Protocol (HRP)
- high speed redundancy protocol (HRP) with redundancy manager
- high speed redundancy protocol (HRP) with standby redundancy

Yes

Yes

Yes

Yes

Yes

Protocol / is supported / Media Redundancy Protocol (MRP)

Yes

Product function

- media redundancy protocol (MRP) with redundancy manager
- redundancy procedure RSTP
- redundancy procedure MSTP

Yes

Yes

Yes

- Passive listening

Yes

Product functions / Security

Product function	
• RADIUS client	Yes
Protocol / is supported	
• SSH	Yes
• SSL	Yes

Product functions / Time

Product function	
• SICLOCK support	Yes
• NTP-client	Yes
• SNTP client	Yes
Protocol / is supported	
• NTP	Yes
• SNTP	Yes

Standards, specifications, approvals

Standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
• for hazardous zone	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
• for hazardous zone / from CSA and UL	ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2

Standards, specifications, approvals / CE

Certificate of suitability / CE marking	Yes
Certificate of suitability / RoHS conformity	Yes

Standards, specifications, approvals / miscellaneous

Certificate of suitability	
• C-Tick	Yes
• E1 approval	Yes
• E1 approval	Yes
• Railway application in accordance with EN 50155	Yes
• Railway application in accordance with EN 50124-1	Yes
• Fire protection in accordance with EN 45545-2	Yes
• KC approval	Yes

Standards, specifications, approvals / ship classification

Marine classification association

• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• Bureau Veritas (BV)	Yes
• DNV GL	Yes
• Korean Register of Shipping (KRS)	Yes
• Polski Rejestr Statkow (PRS)	Yes

Accessories

Product extension / optional / C-PLUG	Yes
---------------------------------------	-----

Further Information / Internet Links

Internet-Link

• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

08/11/2019 