



Powering Business Worldwide

pe.eaton.com

Class 1 Division 2 Groups A B C & D Hazardous Location Transformer

Z48G28T45CU

UPC:786680115745

Dimensions:

- **Height:** X
- **Length:** X
- **Width:** X

Weight:904 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Class 1 Division 2 Groups A B C &D Hazardous Location Transformer
- **Design:** EPTZ
- **Coil Material:** Copper windings
- **Frame:** 244H
- **Frequency Rating:** 60 Hz
- **Phase:** Three-phase
- **Primary Voltage:** 480 DELTA
- **Secondary Voltage:** 208Y/120V
- **Tap Size:** 2 at -5% FCBN
- **Temperature Rating:** 115°C
- **Volt Ampere Rating:** 45 KVA
- **Weathershield:** Indoor-Outdoor
- **Wiring Connection:** 66A

Supporting documents:

- [Eatons Volume 2-Commercial Distribution](#)
- [Eaton Specification Sheet - Z48G28T45CU](#)

Certifications: No Data



Product compliance: No Data

© 2016 Eaton. All rights reserved.