

MOTION CONNECT 500

MLFB-Ordering data

6FX5002-2DC44-1AC0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Electrical data

Design of the sensor	Motor encoder DRIVE-CLiQ
----------------------	--------------------------

Test voltage, rms Signal conductors	500 V
-------------------------------------	-------

Rated voltage U0/U in accordance with EN 50395 Power conductors	30 V
---	------

Mechanical data

Type of connection cable engine side	M17 SPEED-CONNECT
--------------------------------------	-------------------

Type of connection cable converter side	M17
---	-----

Maximum cable outer diameter	7.1 mm
------------------------------	--------

Smallest bending radius (fixed installation)	35 mm
--	-------

Smallest bending radius (flexible installation)	125 mm
---	--------

Number of bends, max.	100,000
-----------------------	---------

Maximum traversing velocity	30 m/min
-----------------------------	----------

Acceleration horizontal, max	2 m/s ²
------------------------------	--------------------

Tensile stress, max. Fixed installation	80 N/mm ²
---	----------------------

Tensile stress, max. Flexible installation	30 N/mm ²
--	----------------------

Torsional stress	Absolute 30°/m
------------------	----------------

Length	2.0 m
--------	-------



Figure similar

MLFB-Ordering data

6FX5002-2DC44-1AC0

Technical data

Ambient temperature

Operation with permanently installed cable	-20 ... 80 °C
Operation with moving cable	0 ... 60 °C
Storage	-20 ... 80 °C

Kind of connection cable	Basis cable
Material of the cable sheath	PVC DESINA-Color green RAL 6018
Type of insulation	Without CFC and silicone
Standard for behavior in fire: flame resistance	EN 60332-1-1 to 1-3
Oil resistance	EN 60811-2-1 (mineral oil only)
Verification of suitability as authorisation for USA	UL STYLE 2502
Verification of suitability as authorisation for Canada	CSA-N.210.2-M90