

FF3GY -- FRPT Flush Furniture Feed Series-3 Service



FF3GY

Use as a replacement cover for Hubbell PT73FFSDGY and PT73FFSDI or to convert and installed Hubbell PT7FSDGY and PT7FSDI into a furniture feed poke-through. Includes (2) ½" and (1) ¾" conduit fittings.

Product Specifications

Product Type	 Furniture Feeds
Furniture Feed Services	3 Service
Flush Furniture Feed Offering	Replacement Covers
Color	 Gray
Complies with:	UL 514A requirements for scrub water protection.
Fire Rating	For use in 1, 1 1/2, 2, 3 or 4 hour rated unprotected reinforced concrete floors or in 1, 2 or 3 hour rated floors employing steel floor units and concrete topping (D900 series design).
Floor Thickness Range	2 1/4" (over metal deck) to 7" (57.2 to 117.8)
UL Installation Spacing	Minimum of 2 feet on centers and not more than one unit per 65 sq. ft. of floor area in each span.
Cored Hole	3" (76.2) diameter
Conduit Tubes	¾" EMT
Listings	UL Listed
Note:	Not to be used as replacement cover for FRF3GY, FRF3BK or FRF3I service fittings.
Wiring Capacity: 3-Service	Power: Up to six #12 AWG and two #10 AWG type THHN wires or up to ten #12 AWG type THHN wires AND Voice/Data: Up to fifty #22 AWG telephone/data conductors (one 25 pair telephone cable) per each low-voltage opening
Wiring Capacity: Voice/Data Only	Up to 200 #22 AWG telephone/data conductors (or four 25 pair telephone cables).
Wiring Capacity: Rule of Thumb	Any combination of wire that does not exceed .11 sq. in. of total allowable copper cross sectional area is acceptable
UPC Number	78358539535

Weight in LBs	0.5
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

