

Straight Blade Devices

20A, 125V, 2 Pole, 3 Wire Grounding

USB Charger Receptacles



Features

- Weather and Tamper Resistant Commercial Grade
- Two Type C USB Ports
- High Power 5 Amp, 5 Volt USB Output
- USB Ports Rated 10,000 Cycles

Ordering Information

| Description                                                            | Color | UPC Number   | Catalog Number |
|------------------------------------------------------------------------|-------|--------------|----------------|
| Weather and Tamper Resistant 15A/125V Duplex, 5 Amp, 5 Volts USB Ports | Black | 883778309403 | USB20C5BKWR    |

Listings

cULus Listed to UL498, UL1310  
Complies with battery charging specification USB BC1.2  
Compatible with USB 1.1/2.0/3.0 devices, including Apple® products  
Meets Section 406.9 of the NEC making it suitable for outdoor use.

Specifications

|                    |                                        |
|--------------------|----------------------------------------|
| Code Compliance    | Complies with Part 15 of the FCC Rules |
| Electrical Ratings | 15 or 20 Amp, 125V AC                  |
| Port Rating        | 5 Amp, 5 Volt                          |
| Indicator          | Green LED                              |
| Contacts           | Brass                                  |
| Terminal Screws    | Stainless Steel                        |
| Mounting Strap     | Brass                                  |
| Mounting Screws    | Stainless Steel                        |
| USB Port           | Stainless Steel                        |

Performance

|                       |                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------|
| <b>Electrical</b>     |                                                                                                                         |
| Current Interruption  | Certified at full rated current                                                                                         |
| Dielectric Voltage    | Withstands 1,500V minimum                                                                                               |
| <b>Mechanical</b>     |                                                                                                                         |
| USB Ports             | Stainless steel rated for 10,000 plug incertions and removal                                                            |
| <b>Environmental</b>  |                                                                                                                         |
| Flammability          | UL 94V-2                                                                                                                |
| Operating Temperature | Maximum continuous 75°C, minimum -40°C (w/o impact)                                                                     |
| Outdoor Suitability   | UL 746C f1                                                                                                              |
| Weather Resistance    | Weather Resistant Device suitable for use outdoor with 3R extra duty protected enclosure, in compliance with NEC 406.15 |



20A WEATHER RESISTANT (WR) DEVICE

Online Resources

- Customer Use Drawing
- eCatalog
- Installation Instructions

