



*Powering Business Worldwide*

[pe.eaton.com](http://pe.eaton.com)

## Class 1 Division 2 Groups A, B, C and D, Hazardous Location Transformer

**Z48G28T30CU**

**UPC:**786680091650

### Dimensions:

- **Height:** 25.5 IN
- **Length:** 12.76 IN
- **Width:** 21.81 IN

**Weight:**603 LB

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Type:** Class 1 Division 2 Groups A, B, C and D, Hazardous Location Transformer
- **Design:** EPTZ
- **Coil Material:** Copper windings
- **Enclosure:** NEMA 3R
- **Frame:** 243H
- **Frequency Rating:** 60 Hz
- **Phase:** Three-phase
- **Primary Voltage:** 480V
- **Secondary Voltage:** 208Y/120V
- **Tap Size:** 2 at -5% FCBN
- **Temperature Rating:** 115°C
- **Volt Ampere Rating:** 30 KVA
- **Weathershield:** Indoor-Outdoor
- **Wiring Connection:** 66A

### Supporting documents:

- [Eaton's Volume 2-Commercial Distribution](#)
- [Eaton Specification Sheet - Z48G28T30CU](#)



**Certifications:**

- UL Listed

**Product compliance:**

- Class I, Div. 2, Groups A, B, C, D

---

© 2016 Eaton. All rights reserved.