



Powering Business Worldwide

pe.eaton.com

Class 1 Division 2 Groups C and D, Hazardous Location Transformer

Z48G22T30SS

UPC:786680009488

Dimensions:

- **Height:** 26.58 IN
- **Length:** 12.76 IN
- **Width:** 25.15 IN

Weight:610 LB

Notes:Grade 304 stainless steel enclosure

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Class 1 Division 2 Groups C and D, Hazardous Location Transformer
- **Design:** EPTZ
- **Coil Material:** Aluminum windings
- **Enclosure:** NEMA 3R
- **Frame:** 243H
- **Frequency Rating:** 60 Hz
- **Phase:** Three-phase
- **Primary Voltage:** 480V
- **Secondary Voltage:** 240 delta/120 midtap
- **Tap Size:** 2 at -5% FCBN
- **Temperature Rating:** 150°C
- **Volt Ampere Rating:** 30 KVA
- **Weathershield:** Indoor-Outdoor
- **Wiring Connection:** 52A

Supporting documents:

- [Class 1, Division 2 Transformers](#)



- [Eatons Volume 2-Commercial Distribution](#)
- [Eaton Specification Sheet - Z48G22T30SS](#)

Certifications:

- UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.