


TECHNICAL DATA SHEET

PMAFLEX - CYF - Corrugated Conduit

Flexible, medium-grade



Flexible conduit ideal for automotive applications



Applications:

- In automobile industry

Features & Benefits:

- Good flexibility
- Good impact strength also at low temperatures and dry conditions
- Self-extinguishing

Materials:

- High-grade, specially formulated polyamide 6

Compatible with:

- PMAFIX Pro, PMAFIX, PMA Smart Line fittings
- PMA accessories

Temperature range:

- -30°C ... +90°C continuous, +125°C short-term

Conforms to:

- NF R 13-903

Weathering resistance:

- Very good UV resistance and weathering characteristics

Colour:

- Black

Chemical properties:

- Please refer to www.pma.ch
(Technical Information / Chemical Resistance)

Environmental properties:


- Free from halogens and cadmium
- RoHS and REACH compliant

CYF-Index									
min.									max.
Ductility									
Fatigue reversed bending									
Compression resistance									
Low temperature performance									
Weathering resistance									

Product selection:

Part no.	Profile	Conduit size		rec. fitting thread size		Dimensions in mm (nom.)			Weight	Packing unit
		NW	metric	PG	metric	d1	d2	stat. R		
CYFT-07B	T	7	10	7	M12x1.5	6.7	10.0	15	2.2	100
CYFT-10B	T	10	12	9	M12x1.5	9.7	12.8	20	2.8	100
CYFT-12B	T	12	16	11	M16x1.5	12.0	15.6	25	3.8	100
CYFT-17B	T	17	20	16	M20x1.5	16.6	21.1	35	6.0	100

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



stat R. : Lowest recommended bending radius for static (fixed) installation

Mechanical Properties:	Value:	Test parameters:	Test method:
Impact strength	> 6 J	(+23°C)	PMA DO 9.21-4330
Compression strength	> 175 N	(50 x 50 mm)	PMA DO 9.21-4320
	> 350 N	(100 x 100 mm)	PMA DO 9.21-4320
Reverse bending resistance	> 15'000 cycles		PMA DO 9.21-4420
	> 40'000 cycles		PMA DO 9.21-4425
Pull-out resistance conduit - fitting series			
PMAFIX IP68	> 250 N		PMA DO 9.21-4610
PMAFIX IP66	> 200 N		PMA DO 9.21-4610

Note: Testing at 23°C, 50% r.h., conduit nominal width 17, unless otherwise stated

Thermal properties:	Value:	Test parameters:	Test method:
Continuous application temperature	-30 ... +90°C		PMA DO 9.21-4510
Upper application temperature	+110°C	(20'000 h)	PMA DO 9.21-4360
Short-term	+125°C	(168 h)	PMA DO 9.21-4360

Fire safety properties:	Value:	Test parameters:	Test method:
Fire performance		compliant	NF R 13-903

ABB Switzerland Ltd,
PMA Cable Protection
Aathalstrasse 90
8610 Uster, Switzerland
Phone: +41 58 585 00 11
pma-info@ch.abb.com
www.pma.ch

Let's write the future.
Together. **abb.com**

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Installation Products Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB Inc. Copyright© 2019 ABB Installation Products Inc. All rights reserved

