



SCALANCE X204-2LD TS; managed IE switch; 4x 10/100 Mbit/s RJ45 ports; 2x 100 Mbit/s Single-mode BFOC; LED diagnostics; Error signaling contact with set button, Redundant power Supply; PROFINET IO device; network management, Redundancy Manager integrated, incl. electron. manual on CD-ROM, C-plug optional

Product type designation	SCALANCE X204-2LD TS
Transfer rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / Integrated	
Number of electrical connections	
• for network components or terminal equipment	4
Number of 10/100 Mbit/s RJ45 ports / Integrated	
• with securing collar	4
Number of 100 Mbit/s ST(BFOC) ports	
• for single mode (LD)	2
Interfaces / other	
Number of electrical connections	
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block

design of the removable storage	
• C-PLUG	Yes
Signal inputs/outputs	
Operating voltage / of the signaling contacts	
• at DC / Rated value	24 V
Operating current / of the signaling contacts	
• at DC / maximum	0.05 A
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage	
• external	12 V
• external / minimum	10 V
• external / maximum	30 V
Supply voltage / at DC	24 V
• rated value	10 ... 30 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	3 A / 32 V
Consumed current / maximum	0.6 A
Power loss [W]	
• at DC / at 24 V	6.6 W
Ambient conditions	
Ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
• Note	In the case of horizontal mounting position of the IE switch X-204-2LD-TS, a maximum ambient temperature of +40 °C is permitted
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20
Design	compact
Width	60 mm
Height	125 mm
Depth	124 mm
Net weight	0.78 kg
Product feature / conformal coating	Yes
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
• S7-300 rail mounting	Yes
• S7-1500 rail mounting	No

Product features, product functions, product components / general

Cascading in the case of a redundant ring / at reconfiguration time of <~0.3~s	100
Cascading in cases of star topology	any (depending only on signal propagation time)

Product functions / management, configuration, engineering

Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	Yes
• Port mirroring	Yes
• multiport mirroring	No
• with IRT / PROFINET IO switch	No
• PROFINET IO diagnosis	Yes
PROFINET conformity class	B
Product function / switch-managed	Yes
Protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	No
• DCP	Yes
• LLDP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher-level designation/location designation	Yes

Product functions / Diagnostics

Product function	
• Port diagnostics	Yes
• Statistics Packet Size	Yes
• Statistics packet type	Yes
• Error statistics	Yes

Product functions / DHCP

Product function	
• DHCP client	Yes
Product functions / redundancy	
Product function	
• Ring redundancy	Yes
• High Speed Redundancy Protocol (HRP)	Yes
• high speed redundancy protocol (HRP) with redundancy manager	Yes
• high speed redundancy protocol (HRP) with standby redundancy	No
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes
Product function	
• media redundancy protocol (MRP) with redundancy manager	Yes
• Passive listening	Yes
Product functions / Security	
Protocol / is supported	
• SSH	Yes
Product functions / time	
Product function	
• SICLOCK support	Yes
Protocol / is supported	
• NTP	No
• SNTP	Yes
Standards, specifications, approvals	
Standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
• for hazardous zone	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
• for hazardous zone / from CSA and UL	ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
Standards, specifications, approvals / CE	
Certificate of suitability / CE marking	Yes
Standards, specifications, approvals / other	
Certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes

- Railway application in accordance with EN 50155
- Railway application in accordance with EN 50121-4
- Railway application in accordance with EN 50124-1
- KC approval

Yes
Yes
No
Yes

Standards, specifications, approvals / marine classification

Marine classification association

- American Bureau of Shipping Europe Ltd. (ABS)
- Bureau Veritas (BV)
- Det Norske Veritas (DNV)
- Germanische Lloyd (GL)
- DNV GL
- Korean Register of Shipping (KRS)
- Lloyds Register of Shipping (LRS)
- Nippon Kaiji Kyokai (NK)
- Polski Rejestr Statkow (PRS)
- Royal Institution of Naval Architects (RINA)

Yes
Yes
No
No
Yes
Yes
Yes
Yes
Yes
Yes

Standards, specifications, approvals / Product conformity

MTBF

85.01 y

Further information / Internet-Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>
<http://www.siemens.com/simatic-net>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

11/11/2019 