

SIMATIC PCS 7, PS 405 10A R XTR S7-400 power supply Wide range, 24/48/60 V DC; 5 V DC/10 A, for redundant use, ATEX approbation identifier for extended temperature range and with conformal coating

Supply voltage

Rated value (DC)

• 24 V DC	Yes
• 48 V DC	Yes
• 60 V DC	Yes

Mains buffering

• Mains/voltage failure stored energy time	20 ms
• Mains buffering according to NAMUR recommendation	Yes

Input current

Rated value at 24 V DC	4 A
Rated value at 48 V DC	2 A
Rated value at 60 V DC	1.6 A
Inrush current, max.	18 A; Full width at half maximum 20 ms

Output voltage

Type of output voltage	DC
Rated value (DC)	
• 5 V DC	Yes
• 24 V DC	Yes

Output current

for backplane bus (5 V DC), max.	10 A; no base load required
for backplane bus (24 V DC), max.	1 A; idling-proof
Short-circuit protection	Yes

Power

Active power input, typ.	95 W
--------------------------	------

Power loss

Power loss, typ.	20 W
------------------	------

Battery

Backup battery

• Backup battery (optional)	Yes; 2x lithium AA; 3.6 V / 2.2 Ah
-----------------------------	------------------------------------

Hardware configuration

Slots	
• required slots	2
Potential separation	
primary/secondary	Yes
Isolation	
Overvoltage category	II
Degree and class of protection	
Equipment protection class	I, with protective conductor
Standards, approvals, certificates	
FM approval	Yes; Ta: 0 °C to 70 °C T4
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	70 °C
Connection method	
Design of electrical connection	3x 1.5 mm ² , solid or stranded wire with end sleeve, external diameter 3 mm to 9 mm
Dimensions	
Width	50 mm
Height	290 mm
Depth	217 mm
Weights	
Weight, approx.	1 200 g
last modified:	03/17/2020