

Product type designation

KEY-PLUG XM-400 LAYER 3 ROUTING

KEY-PLUG XM-400, removable data storage medium for activating Layer 3 features for SCALANCE XM-400 and for simple device replacement in case of fault, and for Recording of configuration data



Ambient conditions

Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20
Width	24.3 mm
Height	17 mm
Depth	8.1 mm
Net weight	5 g
design of the removable storage	
• C-PLUG	No
• KEY-PLUG	Yes

Product features, product functions, product components / general

Storage capacity	256 Mibyte
------------------	------------

Standards, specifications, approvals

Reference code

- according to IEC 81346-2:2018

CFA

Further information / Internet-Links

Internet-Link

- to website: TIA Selection Tool
- to website: Selector SIMATIC NET SELECTION TOOL
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>

<http://www.siemens.com/snst>

<http://www.siemens.com/iwlan>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

11/11/2019