

Product type designation

SpliT Connect M12 Jack

PROFIBUS PA SpliTConnect M12 jack, Connection element for direct connection of PB PA field devices with M12 interface to PB FC
1 pack=5 units



Transfer rate

Transfer rate

- with PROFIBUS PA

31.25 kbit/s

Interfaces

Number of electrical connections

- for PROFIBUS cables

1

Type of electrical connection

- for PROFIBUS cables

integrated insulation displacement contacts

Ambient conditions

Ambient temperature

- during operation
- during storage
- during transport

-40 ... +85 °C

-40 ... +85 °C

-40 ... +85 °C

Protection class IP

IP67

Product features, product functions, product components / general

Product feature

- silicon-free

Yes

Further information / Internet-Links

Internet-Link

- to website: Selector SIMATIC NET
SELECTION TOOL <http://www.siemens.com/snst>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

last modified:

11/11/2019