

Twist-Lock® Devices

30A, 125/250V AC, 3 Pole, 4 Wire Grounding

Watertight Safety-Shroud® Reverse Service Connector

- Features
- Alignment arrows with lock and unlock symbols provide a visual indication that devices are properly connected
 - Superior cord grip design protects terminations from excess strain
 - UL Type 4X Environmental seal protects connection while in use.

Ordering Information

Description	Cord Diameter	UPC	Catalog Number
Reverse service, black housing, white clamps.	.350"-1.150"(9-29)	783585231792	HBL2713SR

Standards

Listed to UL 498
Fed.Spec. W-C-596
Certified to CSA C22.2 No.42

Specifications

Housing / Cord Clamp	PBT
Terminal Retainer	Clear polycarbonate
Contacts	Brass
Terminal Screws	#10-32 Brass (Phillips / Slotted / Robertson)
Terminal Clamp	Cold rolled steel – nickel plated
Assembly Screws	Stainless Steel
Watertight Gland	Neoprene

Performance

Electrical	
Current Interrupting	Certified for current interrupting at full rated current
Dielectric Voltage	Withstands 2,000V minimum
Mechanical	
Terminal Accommodation	#16 AWG - #8 AWG stranded copper wire only.
Terminal Identification	Terminals identified in accordance with UL 498
Environmental	
Flammability	HB or better per UL94/CSA 22.2 No.0.17
Moisture Resistance	IP20 Suitability
Operating Temperatures	Maximum Continuous 75°C; Minimum -40°C (w/o impact)

Accessories

Watertight Safety Shroud Reverse	HBL2715SWR
----------------------------------	------------

Online Resources

eCatalog

