



Powering Business Worldwide

pe.eaton.com

M22 Non-Illuminated Emergency Stop Contact Block

M22-KC01SMC10

UPC:786685476476

Dimensions:

- **Height:** 1.03 IN
- **Length:** 1.46 IN
- **Width:** 1.18 IN

Weight: .085 LB

Notes: All NC contact blocks are positively driven contact

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Contact Block
- **Actuator:** Base, Screw
- **Color:** Black
- **Contact Configuration:** SMCB, NC
- **Environmental Rating:** IP66, NEMA 4X, 13
- **Size:** 22.5 mm
- **Series:** M22

Supporting documents:

- [Eaton's Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [M22 Operators and Accessories](#)
- [M22 Pilot Devices](#)
- [Global Data Sheet - M22-KC01SMC10](#)
- [Eaton Specification Sheet - M22-KC01SMC10](#)

Certifications:

- CCC Marked
- CSA Certified



- Lloyd's Register Certified

Product compliance:

- Bureau Veritas
- CE Marked
- GoST-R