



Powering Business Worldwide

pe.eaton.com

Class 1 Division 2 Groups C and D, Hazardous Location Transformer

Z48N11S15XCUS

UPC:786680053054

Dimensions:

- **Height:** 23.47 IN
- **Length:** 14.1 IN
- **Width:** 22.6 IN

Weight:448 LB

Notes:Grade 304 stainless steel enclosure

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Class 1 Division 2 Groups C and D, Hazardous Location Transformer
- **Design:** EPZ
- **Coil Material:** Copper windings
- **Enclosure:** NEMA 3R
- **Frame:** 182H
- **Frequency Rating:** 50-60 Hz
- **Phase:** Single-phase
- **Primary Voltage:** 480V
- **Secondary Voltage:** 120/240V
- **Tap Size:** NONE
- **Temperature Rating:** 115°C
- **Volt Ampere Rating:** 15 KVA
- **Weathershield:** Indoor-Outdoor
- **Wiring Connection:** 524H

Supporting documents:

- [Eaton's Volume 2-Commercial Distribution](#)



- [Eaton Specification Sheet - Z48N11S15XCUS](#)

Certifications:

- UL Listed

Product compliance: No Data