



Powering Business Worldwide

pe.eaton.com

25 KVA CL1 DIV 2 HAZ LOC XFMR 1PH 480V-120/240V 115C

Z48G11S25CU

UPC:786680056871

Dimensions:

- **Height:** 18.06 IN
- **Length:** 14.12 IN
- **Width:** 16.35 IN

Weight:392 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Class 1 Division 2 Groups C and D, Hazardous Location Transformer
- **Design:** EPZ
- **Coil Material:** Copper windings
- **Enclosure:** NEMA 3R
- **Frame:** 182H
- **Frequency Rating:** 60 Hz
- **Phase:** Single-phase
- **Primary Voltage:** 480V
- **Secondary Voltage:** 120/240V
- **Tap Size:** 2 at -5% FCBN
- **Temperature Rating:** 115°C
- **Volt Ampere Rating:** 25 KVA
- **Weathershield:** Indoor-Outdoor
- **Wiring Connection:** 2D

Supporting documents:

- [Eatons Volume 2-Commercial Distribution](#)
- [Eaton Specification Sheet - Z48G11S25CU](#)

Certifications:



- UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.