

Kellems® Wire Management Products  
Strain Relief Grips  
Deluxe Cord Grips

HUBBELL

Features

- Nylon Fitting
- Stainless steel mesh is corrosion resistant
- Neoprene bushing is oil and watertight

Ordering Information

| Description                                             | Form Size | UPC          | Catalog Number |
|---------------------------------------------------------|-----------|--------------|----------------|
| Stainless Steel Fittings and Mesh, Straight Male Thread | F2        | 783585338149 | CG610SST       |

Listings

UL Listed  
CSA Certified

Online Resources

eCatalog



Specifications

|                 |                 |
|-----------------|-----------------|
| Strand          | Stainless Steel |
| Fittings        | Stainless Steel |
| Bushings        | Neoprene        |
| NPT Thread Size | 3/4 Inch        |

Performance

Environmental

|                        |                                                                                                             |
|------------------------|-------------------------------------------------------------------------------------------------------------|
| Flammability           | UL 94HB (Strand grip), UL 94V-2(Fitting)                                                                    |
| Hazardous Locations    | Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C |
| Operating Temperatures | –30°F to +240°F (–34°C to +115°C)                                                                           |
| Wet Locations          | Suitable for use in wet locations when used with a listed sealing ring between box and fitting              |

