



Figure similar

POWER SUPPLY; PHASES:3; PN(KW):0,48;
UPRI(V):400+/-20; USEC(V DC):24; ISEC(A DC):20/24
(60/40 CEL); F(HZ):50...60; VECTOR GR./SHIELD
WNG.:YD1 /0; PROTECTION CL.:I; TA/ISOKL:60 /B;
W(%):4,2; IP00; TYPE OF TERMINALS:SCREW
CONNECTION; INSTALLATION:SCREW; EN 61558-2-
6, EN61131-2 >UL/CSA-RECOGNIZED< >SAFETY
ISOLATING TRANSFORMER<

General technical data:		
Product designation		4AV3200-2EB00-0A
Product brand name		SIDAC
Vector group		Ii0
Certificate of suitability		CE
Product function		
• Temperature monitoring		No
• Insulation monitoring		No
• Short-circuit and overload proof		No
• varistor protective wiring		Yes
Operating resource protection class		I
Number of shielding windings		0
Inputs:		
Phase number of the inputs		3
Type of current of the inputs		AC
Input voltage		
• _1 rated value	V	420

• _2 rated value	V	400
• _3 rated value	V	380
Electrical input frequency		
• minimum	Hz	50
• maximum	Hz	60
Input voltage		
• minimum	V	342
• maximum	V	445.2
Type of electrical connection at input for main current circuit		screw-type terminals

Outputs:

Type of current		
• _1 at output		DC
Output voltage		
• _1 rated value	V	24
Output voltage of the measurement signal at analog output at DC maximum	V	28.8
Output voltage of the measurement signal at analog output at DC minimum	V	20.4
Output current		
• _1 rated value	A	20
Type of electrical connection at output for main current circuit		screw-type terminals
Relative residual ripple		
• of the output voltage 1 for main current circuit maximum	%	5

Ambient conditions:

Thermal class acc. to IEC 60085		B
Ambient temperature rated value	°C	60
Protection class IP		IP00

Mechanical data:

Mounting type		screws
Construction form of the iron core		3UI 90/30
Width	m	216
Height	m	220
Depth	m	115

Certificates/ approvals:

General Product Approval	Declaration of Conformity	Shipping Ap- proval	other
 UL		 EG-Konf.	 PRS

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4AV3200-2EB00-0A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4AV3200-2EB00-0A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4AV3200-2EB00-0A&lang=en

last modified:

10/18/2018