



Powering Business Worldwide

pe.eaton.com

Class 1 Division 2 Groups A, B, C, & D Hazardous Location Transformer

Z48G22T06X

UPC:786680108815

Dimensions:

- **Height:** 17.78 IN
- **Length:** 10.52 IN
- **Width:** 25.18 IN

Weight:282 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Class 1 Division 2 Groups A, B, C, &D, Hazardous Location Transformer
- **Design:** EPTZ
- **Coil Material:** Aluminum windings
- **Enclosure:** NEMA 3R
- **Frame:** 95H
- **Frequency Rating:** 50-60 Hz
- **Phase:** Three-phase
- **Primary Voltage:** 480V
- **Secondary Voltage:** 240/120V
- **Tap Size:** 2 at -5% FCBN
- **Temperature Rating:** 115°C
- **Volt Ampere Rating:** 6 KVA
- **Weathershield:** Indoor-Outdoor
- **Wiring Connection:** 52A

Supporting documents:

- [Eaton's Volume 2-Commercial Distribution](#)
- [Eaton Specification Sheet - Z48G22T06X](#)



Certifications:

- UL Listed
- CSA Certified

Product compliance: No Data

© 2016 Eaton. All rights reserved.