

Product type designation

SpliT Connect Tap

PROFIBUS PA SpliTConnect TAP; for setting up PROFIBUS PA segments and connection of PA field devices, insulation displacement method, IP67 Type of delivery: 10 units=1 pack



Transfer rate

Transfer rate

- with PROFIBUS PA

31.25 kbit/s

Interfaces

Number of electrical connections

- for PROFIBUS cables

3

Type of electrical connection

- for PROFIBUS cables

integrated insulation displacement contacts

Mechanical data

Material / of the enclosure

PBT (polybutyleneterephthalate)

Design, dimensions and weight

Width

84 mm

Height

54 mm

Depth

49 mm

Net weight

170 g

Mounting type

- 35 mm DIN rail mounting

Yes

- wall mounting

Yes

Permitted ambient conditions

Ambient temperature

- during operation
- during storage
- during transport

-40 ... +85 °C

-40 ... +85 °C

-40 ... +85 °C

Protection class IP

IP67

Product properties, functions, components / general

Product feature

- silicon-free

Yes

Standards, specifications, approvals

Certificate of suitability

- UL approval

Yes

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

08/12/2019