



*Powering Business Worldwide*

[pe.eaton.com](http://pe.eaton.com)

## Class 1 Division 2 Groups A, B, C, & D Hazardous Location Transformer

**Z48N11S15CUS6**

**UPC:**786680108785

### Dimensions:

- **Height:** 19.68 IN
- **Length:** 10.53 IN
- **Width:** 19.63 IN

**Weight:**309 LB

**Notes:**Grade 316 stainless steel enclosure (does not imply NEMA 4X rating)

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Type:** Class 1 Division 2 Groups A, B, C, &D, Hazardous Location Transformer
- **Design:** EPZ
- **Coil Material:** Copper windings
- **Enclosure:** NEMA 3R
- **Frame:** 180H
- **Frequency Rating:** 60 Hz
- **Phase:** Single-phase
- **Primary Voltage:** 480V
- **Secondary Voltage:** 120/240V
- **Tap Size:** None
- **Temperature Rating:** 115°C
- **Volt Ampere Rating:** 15 KVA
- **Weathershield:** Indoor-Outdoor
- **Wiring Connection:** 524H

**Supporting documents:**



- [Eatons Volume 2-Commercial Distribution](#)
- [Eaton Specification Sheet - Z48N11S15CUS6](#)

**Certifications:**

- UL Listed
- CSA Certified

**Product compliance:** No Data