

SIPLUS DP PB connector PG socket 90° Cable outlet -40...+70°C
with conformal coating based on 6ES7972-0BB70-0XA0 .
Connection plug for PROFIBUS up to 12 Mbit/s



Figure similar

Transfer rate	
Transfer rate / with PROFIBUS DP	9.6 kbit/s ... 12 Mbit/s
Ambient conditions	
Ambient temperature	
• in horizontal mounting position / during operation	70 ... -40 °C
• during storage and transport	70 ... -40 °C
Installation altitude / at height above sea level / maximum	5000 m
Ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1140 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity	
• with condensation / acc. to IEC 60068-2-38 / maximum	100 %
Resistance to biologically active substances	

• conformity acc. to EN 60721-3-3	Yes; Class 3B2 mold and fungal spores (excluding fauna); Class 3B3 on request
• conformity acc. to EN 60721-3-6	Yes
Resistance to chemically active substances	
• conformity acc. to EN 60721-3-3	Yes; Class 3C4 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
• conformity acc. to EN 60721-3-6	Yes; Class 6C3 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
Resistance to mechanically active substances	
• conformity acc. to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust; *
• conformity acc. to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Environmental category / acc. to IEC 60721 / Note	*. The supplied plug covers must remain in place on the unused interfaces during operation!
Coating / for equipped printed circuit board / acc. to EN 61086	Yes; Class 2 for high availability
Type of coating	
• protection against pollution according to EN 60664-3	Yes
• for electronic devices in railway applications acc. to EN 50155	Yes
Type of test / of the coating / acc. to MIL-I-46058C	Yes; Coating discoloration during service life possible
Product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes; Conformal coating, class A
Protection class IP	IP20

Standards, specifications, approvals

Certificate of suitability	
• RoHS conformity	Yes

Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified:

11/25/2019