



*Powering Business Worldwide*

[pe.eaton.com](http://pe.eaton.com)

## Class 1 Division 2 Groups C and D, Hazardous Location Transformer

**Z48G28B45CUSS**

**UPC:**786680089916

### Dimensions:

- **Height:** 31.98 IN
- **Length:** 15.68 IN
- **Width:** 46.23 IN

**Weight:**1651 LB

**Notes:**Grade 304 stainless steel enclosure

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Type:** Class 1 Division 2 Groups C and D, Hazardous Location Transformer
- **Design:** EPTZ
- **Coil Material:** Copper windings
- **Enclosure:** NEMA 3R
- **Frame:** 245H
- **Frequency Rating:** 60 Hz
- **Phase:** Three-phase
- **Primary Voltage:** 480V
- **Secondary Voltage:** 208Y/120V
- **Tap Size:** 2 at -5% FCBN
- **Temperature Rating:** 80°C
- **Volt Ampere Rating:** 45 KVA
- **Weathershield:** Indoor-Outdoor
- **Wiring Connection:** 66A

### Supporting documents:

- [Eatons Volume 2-Commercial Distribution](#)



- [Eaton Specification Sheet - Z48G28B45CUSS](#)

**Certifications:**

- UL Listed

**Product compliance:** No Data

---

© 2016 Eaton. All rights reserved.