


15 kV 200A Loadbreak Elbow Reference Guide

15 kV Loadbreak (Current)			15 kV Loadbreak (Enhanced)	
		→		
Elbow Connector 165LR-W5X	Elbow Connector w/ Test Point 166LR-W5X		Elbow Connector 161LR-W5X	Elbow Connector w/ Test Point 162LR-W5X
		→		
Jacket Seal Elbow 165LRJS-W5X	Jacket Seal Elbow w/ Test Point 166LRJS-W5X		Jacket Seal Elbow 161LRJS-W5X	Jacket Seal Elbow w/ Test Point 162LRJS-W5X

Applicable Catalog #s	Min (in.)	Max (in.)	Symbol
165LR 166LR 165LRJS 166LRJS	0.575	0.740	A
	0.635	0.905	B
	0.805	1.060	C
	0.890	1.220	D




Symbol	Min (in.)	Max (in.)	Applicable Catalog #s
A	0.575	0.740	161LR 162LR 161LRJS 162LRJS
B	0.635	0.905	
C	0.805	1.060	
D	0.890	1.220	

25 kV 200A Loadbreak Elbow Reference Guide

25 kV Loadbreak (Current)		25 kV Loadbreak (Enhanced)	
			
Elbow Connector 275LR-W5X	Elbow Connector w/ Test Point 276LR-W5X	Elbow Connector 261LR-W5X	Elbow Connector w/ Test Point 262LR-W5X
			
Jacket Seal Elbow 275LRJS-W5X	Jacket Seal Elbow w/ Test Point 276LRJS-W5X	Jacket Seal Elbow 261LRJS-W5X	Jacket Seal Elbow w/ Test Point 262LRJS-W5X

Applicable Catalog #s	Min (in.)	Max (in.)	Symbol
275LR 276LR 275LRJS 276LRJS			
	0.635	0.905	B
	0.800	1.060	CC
	0.940	1.170	DD



Symbol	Min (in.)	Max (in.)	Applicable Catalog #s
A*	0.575	.740	261LR 261LRJS 262LR 262LRJS
B	0.635	.905	
C	0.805	1.060	
D	0.890	1.220	

Applicable Catalog #s	Min (in.)	Max (in.)	Symbol
275LR 276LR 275LRJS 276LRJS	1.090	1.310	E**

No change on
"E" size



Symbol	Min (in.)	Max (in.)	Applicable Catalog #s
E**	1.090	1.310	275LR 276LR 275LRJS 276LRJS

Notes: * New cable entrance size available.

** Size "E" catalog number remains unchanged.