

6" Incandescent Super Sloped Ceiling Downlights

Juno's patented Super Slope Ceiling Downlights are available in new construction or remodel versions for both insulated and non-insulated ceilings.

6" Super Slope Housings – 7/12 to 12/12 Pitch (30° to 45°)



IC Housing
Energy-efficient, Air-Loc® double wall housing can be covered with insulation. Fits 2 x 8 construction.

IC928 with Real Nail® 3 bar hangers
IC928 W with push-in electrical connectors and Real Nail® 3 bar hangers

18½" L x 9½" W x 7⅞" H
Ceiling opening: 6⅞" x 8⅞" oval

AIR-LOC



TC Housing
Requires 3" spacing from insulation. For 2 x 8 or 2 x 10 construction.

TC928 with Real Nail® 3 bar hangers

18½" L x 9½" W
Adjustable fixture height: 7½" to 9⅞"
Ceiling opening: 6⅞" x 8⅞" oval



TC Remodel Housing
Requires 3" spacing from insulation. For 2 x 8 or 2 x 10 construction.

TC928R Remodel Housing

14" L x 7⅞" W
Adjustable fixture height: 7⅞" to 9"
Ceiling opening: 6⅞" x 8¼" oval

Note: In Canada when insulation is present, Type IC fixtures must be used.

6" Standard Super Slope Trims

Downlights



Downlight Baffle
604 WWH White
604 BWH Black
604 BABZ Black
604 BBL Black
604 BSC Black
IC: 90W PAR38
TC: 150W PAR38
For superior baffling, use 75W PAR30



Reflector Cone
602 BWH Black Alzak®
602 CWH Clear Alzak®
602 GWH Gold Alzak®
602 HZSC Haze
602 HZWH Haze
602 WWH White
602 WHZABZ Wheat Haze
602 WHZWH Wheat Haze
IC: 75W PAR30, 90W PAR38, 85W BR30
TC: 75W PAR30, 150W PAR38, 85W BR30

Adjustables



Cylinder Spotlight in Baffle
606 WWH White
606 BWH Black
60W PAR16
45° vertical adjustment, 358° rotation

Lensed



Lensed Shower Trim
Flat Diffuser
603 WWH White
603 BWH Black
IC: 50W PAR30
TC: 75W A19, 75W PAR30



Accessories

Catalog Number	Description
ALG928	Energy Conserving Gasket for Air-Loc® IC928 Housings

Trim Ring Finishes

ABZ Classic Aged Bronze	WH White
SC Satin Chrome	BL Black