


VuLite® 6" Line Voltage Housings and Trims

IC Housings

V6IC W 6" IC New Construction
V6ICN W 6" IC New Construction with Floating Socket

Energy efficient housing.
 May be covered with insulation.

Dimensions:
 13-3/4"L x 13-3/8"W x 7-3/8"H
 Ceiling Cutout: 6-1/2" Diameter




AIR-LOC

V6ICR W

6" IC Remodel
 Energy efficient housing.
 May be covered with insulation.

Dimensions:
 13-3/4"L x 6-3/4"W x 7-3/8"H
 Ceiling Cutout: 6-1/4" Diameter




AIR-LOC

TC Housings

V6TC W

6" TC New Construction
 Requires 3" spacing from insulation.


Dimensions:
 13-3/4"L x 13-3/8"W x 7-3/8"H
 Ceiling Cutout: 6-1/2" Diameter



V6TCR W

6" TC Remodel
 Requires 3" spacing from insulation.

Dimensions:
 13-3/4"L x 6-3/4"W x 7-3/8"H
 Ceiling Cutout: 6-1/4" Diameter




Accessories: **VALG6** Airloc® gasket kit for V6IC W housing when an Airloc® trim is not being used. **G2405** Set of(4) T-bar clips for installation in suspended ceilings.

6" Compatible Trims

Conical Baffle

V3024 WWH White
V3024 BWH Black

Aperture: 5-3/4"
 Outer Diameter: 7-3/4"



Juno Compatible Housings: Lamp Wattage/Type

V6IC W, V6ICR W: 50W PAR30, 75W PAR30L, 65W BR30
V6TC W, V6TCR W: 75W PAR30/PAR30L, 65W BR30, 120W BR40


IC22, IC22R: 50W PAR30, 75W PAR30L, 65W BR30

IC2, TC2, TC2R: 75W PAR30 w/socket extender, 75W PAR30L, 65W BR30

Full Baffle

V3034 WWH White
V3034 BWH Black
V3034T WWH White w/Torsion Springs
V3034T BWH Black w/Torsion Springs

Aperture: 5-3/4"
 Outer Diameter: 7-5/8"



AIR-LOC



Juno Compatible Housings: Lamp Wattage/Type

V6IC W, V6ICN W, V6ICR W: 40W A19*, 75W PAR30/PAR30L, 65W BR30, 90W BR40, 90W PAR38*

V6TC W, V6TCR W: 60W A19*, 75W PAR30/PAR30L, 85W BR30, 120W BR40, 150W PAR38*

IC22, IC22R, IC23: 40W A19, 75W PAR30/PAR30L, 65W BR30, 90W BR40, 90W PAR38

IC2: 60W A19, 75W PAR30/PAR30L, 85W BR30, 100W PAR38, 120W BR40

TC2, TC2R: 60W A19, 75W PAR30/PAR30L, 85W BR30, 150W PAR38, 120W BR40

ICPL6 Series: 32W max. CFL†

PL6 Series: 42W max CFL†


* No A19 listing and 75W PAR38 max. for the V3034B Series

† Note: For best performance, 26W is recommended.

Straight Baffle

V3025 WWH White
V3025 BWH Black

Aperture: 5-3/4"
 Outer Diameter: 7-3/4"



Juno Compatible Housings: Lamp Wattage/Type

V6IC W, V6ICR W: 50W PAR30/PAR30L, 75W PAR38
V6TC W, V6TCR W: 75W PAR30/PAR30L, 65W BR30, 120W BR40, 120W PAR38

IC22, IC22R: 75W PAR30/PAR30L, 65W BR30, 75W PAR38
IC2: 75W PAR30 w/socket extender, 75W PAR30L, 65W BR30, 90W PAR38, 100W BR40

TC2, TC2R: 75W PAR30 w/socket extender, 75W PAR30L, 65W BR30, 150W PAR38, 120W BR40

Patent Pending

Clear Cone

V3027C WH: Clear

Aperture: 5-3/4"
 Outer Diameter: 7-3/4"



Juno Compatible Housings: Lamp Wattage/Type

V6IC W, V6ICR W: 50W PAR30, 75W PAR30L, 65W BR30
V6TC W, V6TCR W: 75W PAR30/PAR30L, 65W BR30, 90W BR40

IC2, IC22, IC22R: 50W PAR30, 75W PAR30L, 65W BR30

TC2, TC2R: 75W PAR30/PAR30L, 65W BR30

VuLite® 6" Line Voltage Housings and Trims

6" Compatible Trims

Full Cone

V3037 WWH White

V3037T WWH White w/Torsion Springs

Aperture: 5-3/4"


Outer Diameter: 7-5/8"



Stippled Opal Lens Shower with Reflector

V3040N PW Plastic White

Outer Diameter: 8"



Juno Compatible Housings: Lamp Wattage/Type

V6IC W, V6ICN W, V6ICR W: 40W A19, 75W PAR30/PAR30L, 65W BR30, 75W BR40, 90W PAR38

V6TC W, V6TCR W: 60W A19, 75W PAR30/PAR30L, 85W BR30, 120W BR40, 150W PAR38

IC22, IC22R, IC23: 40W A19, 75W PAR30/PAR30L, 65W BR30, 90W BR40, 90W PAR38

IC2: 60W A19, 75W PAR30/PAR30L, 85W BR30, 100W PAR38

TC2, TC2R: 60W A19, 75W PAR30/PAR30L, 85W BR30, 120W BR40, 150W PAR38

ICPL6 Series: 32W max. CFL[†]

PL6 Series: 42W max CFL[†]

[†]Note: For best performance, 26W is recommended.

Juno Compatible Housings: Lamp Wattage/Type

V6IC W, V6ICN W, V6ICR W: 34W A19, 35W PAR30

V6TC W, V6TCR W: 75W A19

IC2, IC22, IC22R, IC23: 40W A19


TC2, TC2R: 75W A19

ICPL6/PL6 Series: 13W max. CFL

Drop Opal Lens Shower with Reflector

V3041 PW Plastic White

Outer Diameter: 8"



Eyeball

V3029 WH White

Outer Diameter: 7-3/4"



Juno Compatible Housings: Lamp Wattage/Type

V6IC W, V6ICN W, V6ICR W: 65W BR30, 75W PAR30L

V6TC W, V6TCR W: 75W PAR30/PAR30L, 65W BR30

IC22, IC22R, IC23, IC2, TC2, TC2R: 75W PAR30 w/socket extender, 75W PAR30L, 65W BR30

Juno Compatible Housings: Lamp Wattage/Type

V6IC W, V6ICN W, V6ICR W: 40W A19

V6TC W, V6TCR W: 100W A19

IC22, IC22R, IC23: 40W A19

IC2: 60W A19

TC2, TC2R: 100W A19

ICPL6/PL6 Series: 26W max. CFL

Stippled Opal Lens Shower

V3020 PW Plastic White

Outer Diameter: 8"




Open Frame

V3050 WH White

Aperture: 3-7/8"

Outer Diameter: 8"



Juno Compatible Housings: Lamp Wattage/Type

V6IC W, V6ICR W, V6TC W, V6TCR W: 65W BR30



All trademarks referenced are property of their respective owners. Specifications subject to change without notice. Printed in the U.S.A.