



Project: _____

Fixture Type: _____

Location: _____

Contact/Phone: _____

4" MINIATURE UNIVERSAL TC NEW CONSTRUCTION HOUSING

INCANDESCENT LAMPS

TC1 SERIES

PRODUCT DESCRIPTION

TC New Construction Housing design for use in non-insulated areas
 • If installed where insulation is present, the insulation must be pulled back 3" from all sides of the TC housing.

PRODUCT SPECIFICATIONS

Lamp Lamp ratings based on trim selected – see page 2.

Socket Detachable medium base porcelain with nickel-plated copper screw shell.

Trims Trim selection shown on page 2.

Labels UL listed for through-branch wiring, damp locations and IP
 • Product thermally protected against improper use of lamps or insulation
 • Union made • UL Listed/CSA certified • Trim No. 11, 12, 4101, 4102 and 4181 are wet location approved for covered ceiling applications
 • Trims 14, 17 are wet location approved for covered ceiling applications, **when used with outdoor rated lamps**.

Testing All reports are based on published industry procedures; field performance may differ from laboratory performance.
 Specifications subject to change without notice.

INSTALLATION

Real Nail® Bar Hangers Telescoping, Patented (US Patent D552,969) Real Nail 3 and Real Nail 2 systems permits quick placement of housing anywhere within 24" O.C. joists or suspended ceilings • Bars scored in two locations for fast, clean breaking, allowing housing installation in tight applications • Bars captive to mounting frame • Edge-mounted for extra strength • Quick-Loc slot (location identified on the mounting frame) and oversized locking set screw lock fixture in position • May be installed either perpendicular or parallel to junction box.

Real Nail 3 Bar Hanger Integral T-bar notch and clip secures housing in suspended ceiling grid – no accessory clips required • 24" expansion stop allows quick placement of fixture in standard grid spacing
 • Captive bugle-headed ring shank nail for quick one-step installation and easy removal with claw hammer for fixture relocation • Bar hanger foot contoured to align to bottom of construction joist • Alternate mounting holes included.


Real Nail 2 Bar Hanger (S options) Small bar hanger foot designed to install directly on strapping construction material • Features Real Nail captive nail system for quick one-step installation • G2405 accessory clips required for suspended ceiling installation.

Junction Box Pre-wired junction box provided with (5) ½" and (1) ¾" knockouts, (4) Non-metallic sheathed cable connectors and ground wire, U.L. listed/CSA certified for through-branch wiring, maximum 8 No. 12 AWG 90° C branch circuit conductors (4 in, 4 out) • Junction box provided with removable access plates • Knockouts equipped with pryout slots.

Mounting Frame 22-gauge die-formed galvanized steel mounting frame • 9 5/8" L x 6 3/4" W, (excluding bar hangers) • Rough-in section (junction box, mounting frame, housing and bar hangers) fully assembled for ease of installation.

Housing TC housing, 22-gauge galvanized steel • Housing is vertically adjustable to accommodate up to a 1 1/4" ceiling thickness.

DIMENSIONS



Accessories

Catalog Number	Description
4TSA	4" Housing Trim Adapter
GU10WHIP	Medium Base to GU10 Adapter
G2405	T-Bar Clips (Set of 4), for S option only

To order, specify catalog number.

PRODUCT CODES

Catalog Number	Input Voltage	Lamp Rating
TC1	120V	R14/R16/R20/PAR16/PAR20 (See page 2 for max. trim rating)
TC1 S	120V	R14/R16/R20/PAR16/PAR20 (See page 2 for max. trim rating)

Housing and trim can be ordered together or separate, but will always ship separately.

4" MINIATURE UNIVERSAL TC NEW CONSTRUCTION HOUSING

INCANDESCENT LAMPS

TC1 SERIES

TRIMS/LAMPS

	Catalog Number	Description	Max. Lamp Rating		Catalog Number	Description	Max. Lamp Rating
	13 WH	2" Pinhole with Integral Shield	50W PAR20/50W R20		4150 MESHSC	Cylinder, Mesh Glass, Satin Chrome Trim Ring	50W PAR20, 50W R20
	14 BWH ♦♦	Black Baffle, White Trim Ring	50W PAR20/50W R20		4180 FROST	Solid Glass Collar Trim, Frosted Glass (torsion spring attachment)	50W PAR20, 50W R20
	14 BSC ♦♦	Black Baffle, Satin Chrome Trim Ring			4181 CLEAR ♦	Perimeter Frosted Clear Glass (torsion spring attachment)	50W PAR20, 50W R20
	14 BABZ ♦♦	Black Baffle, Classic Aged Bronze Trim Ring			175Q HZWH ♦♦	Square Downlight, Haze, White Trim Ring	50W PAR20, 30W R20
	14 BBL ♦♦	Black Baffle, Black Trim Ring			175Q WWH ♦♦	Square Downlight, White, White Trim Ring	
	14 WWH ♦♦	White Baffle, White Trim Ring			175Q BWH ♦♦	Square Downlight, Black, White Trim Ring	
	17 CWH ♦♦	Clear Alzak® Cone, White Trim Ring	50W PAR20/50W R20		175Q WHZWH ♦♦	Square Downlight, Wheat Haze Reflector	
	17 GWH ♦♦	Gold Cone, White Trim Ring			135Q WH	Square Pinhole, White	50W PAR20, 50W R20
	17 BWH ♦♦	Black Cone, White Trim Ring			440SQ WH	Square Flush Gimbal, White	50W MR16 120V GU10 Base (Requires GU10WHIP)
	17 PTSC ♦♦	Pewter Cone, Satin Chrome Trim Ring			440SQ BL	Square Flush Gimbal, Black	35° Vertical Adjustment
	17 WWH ♦♦	White Cone, White Trim Ring			125Q WWH ♦	Square Frosted Lens w/Clear Center White, White Trim Ring	50W PAR20, 50W R20
	17 HZWH ♦♦	Haze Cone, White Trim Ring			GU10WHIP	Medium Base to GU10 Adapter	
	17 WHZWH ♦♦	Wheat Haze Cone, White Trim Ring					
	17 WHZABZ ♦♦	Wheat Haze Cone, Classic Aged Bronze Trim Ring					
	10 WH	Push-In Flush Gimbal Ring, White	50W PAR20/ 75W ES20 GU10 (Requires GU10WHIP)				
	10 BL	Push-In Flush Gimbal Ring, Black					
	10 SC	Push-In Flush Gimbal Ring, Satin Chrome					
	10 ABZ	Push-In Flush Gimbal Ring, Classic Aged Bronze					
	18 WH	Mini Eyeball, White	60W PAR16, 40W R16				
	18 SC	Mini Eyeball, Satin Chrome					
	19 WH	Mini Eyeball, White	40W R14/40W R16 intermediate screw base				
	440 WH	Flush Gimbal Ring, White	50W MR16, 50W PAR16, 50W ES16 GU10 (Requires GU10WHIP)				
	440 BL	Flush Gimbal Ring, Black					
	440 SC	Flush Gimbal Ring, Satin Chrome					
	440 ABZ	Flush Gimbal Ring, Classic Aged Bronze (uses 2" optical media)					
	445 WH	Adjustable Slot Aperture, White	50W MR16, 50W PAR16, 50W ES16 GU10 (Requires GU10WHIP)				
	448 WH	Eyeball, White w/Black Baffle	50W MR16, 50W PAR16, 50W ES16 GU10 (Requires GU10WHIP)				
	448 SC	Eyeball, Satin Chrome w/Black Baffle					
	11 WH ♦	Drop Opal, White	50W PAR20/50W R20				
	12 WWH ♦	Perimeter Frosted Lens, White Trim Ring	50W PAR20/50W R20				
	12 WSC ♦	Perimeter Frosted Lens, Satin Chrome Trim Ring					
	12 WABZ ♦	Perimeter Frosted Lens, Classic Aged Bronze Trim Ring					
	16 WH	Scoop Wall Wash w/higher inner shield, White	40W R14/40W R16 intermediate screw base				
	446 WH	Adjustable Scoop, White	50W MR16, 50W PAR16, 50W ES16 GU10 (Requires GU10WHIP)				
	4101 WH ♦	Beveled Dome Shower, White	50W PAR20, 50W R20				
	4101 SC ♦	Beveled Dome Shower, Satin Chrome					
	4101 ABZ ♦	Beveled Dome Shower, Classic Aged Bronze					
	4102 WH ♦	Beveled Shower, White	50W PAR20, 50W R20				
	4102 SC ♦	Beveled Shower, Satin Chrome					
	4102 ABZ ♦	Beveled Shower, Classic Aged Bronze					
	4103 FROSTWH	Beveled Cylinder, Frosted Glass, White Trim Ring	50W PAR20, 50W R20				
	4103 FROSTSC	Beveled Cylinder, Frosted Glass, Satin Chrome Trim Ring					
	4104 HZSC	Beveled Haze Cone, Satin Chrome Trim Ring	50W PAR20, 50W R20				
	4104 WHZABZ	Beveled Wheat Haze Cone, Classic Aged Bronze Trim Ring					

Trim Size: 5" O.D.

Alzak is a registered trademark of Alcoa Corp.

Note: In Canada when insulation is present, Type IC fixtures must be used.

♦ UL Listed for use in wet location.

♦♦ UL Listed for use in wet location with outdoor rated lamp.

Housing and trim can be ordered together or separate, but will always ship separately.