


Multimeter Fuses

Multimeter Replacement Fuses



69033



69191

Cat. No.	For Use With	Fuse Type
69191	MM1000, MM1300, MM2000, MM2300, MM6000	F 11A/1000V
69192	MM1000, MM1300, MM2000, MM2300, MM6000	F 440mA/1000V
69193	MM100 Fuse Kit	F10A/500V, F250mA/250V
69194	MM200 Fuse Kit	F10A/500V, F400mA/250V
69031	MM300	5x20 200MA 600V
69032	MM300, MM400	6x32 10A 600V
69033	MM400	5x20 500MA 600V
69034	MM600, MM700	10x38 10A 1000V
69035	MM600, MM700	6x32 500MA 1000V

Meter Kits

Electrical Maintenance & Test Kit

- Cat. No. RT210 detects the most common wiring problems in standard and GFCI receptacles including open ground, reverse polarity, open hot, open neutral, and hot/ground reversed
- Cat. No. 69409 Line splitter 10x allows the measuring of current draw up to 15A without splitting the load's power cord
- Cat. No. CL110 has CAT III 600V, Class 2, Double insulation safety rating and features a backlit display for clear readings
- RT210 withstands a 6.6 ft. (2 m)
- Includes a carrying case, test leads and batteries



Cat. No.	Set Contains				Weight
CL110KIT					0.94 lb (430.0 g)
Cat. No.	Overall Length	Overall Height	Overall Width	Batteries	
CL110	8.70" (221.1 mm)	1.61" (40.9 mm)	3.02" (76.6 mm)	3 x AAA	
RT210	1.62" (41.3 mm)	2.88" (73.0 mm)	1.88" (47.6 mm)	—	
69409	4.67" (118.6 mm)	4.67" (118.6 mm)	2.28" (57.9 mm)	—	



CL110KIT

Electrical Test Kit

- The MM300 multimeter was developed to withstand daily wear and tear on the job site, and has a safety rating of CAT III 600V, Class 2, Double insulation
- The NCVT-1 has a bright green LED to indicate the tester is working; it changes to red and warning tones sound when voltage is detected
- NCVT-1 has a digitally-controlled ON/OFF power button and auto power-off feature to conserve and extend battery life
- Receptacle tester detects wiring configurations and indicates correct wiring, open ground, open hot, open neutral, hot/ground reversed; it does not indicate quality of ground, multiple hot wires, or a combination of defects
- Includes visual and audible continuity indicators up to 25Ω
- Includes test leads and batteries



Cat. No.	Set Contains	Weight
69149		0.94 lb (430.0 g)

Cat. No.	Overall Length	Overall Height	Overall Width	Batteries
MM300	6.00" (152.4 mm)	1.78" (45.2 mm)	3.16" (80.4 mm)	2 x AAA
NCVT-1	5.50" (139.7 mm)	1.00" (25.4 mm)	0.72" (18.3 mm)	2 x AAA
Receptacle Tester	2.75" (69.9 mm)	1.00" (25.4 mm)	1.50" (38.1 mm)	—



69149



Electrical Testers

Non-Contact Voltage Testers

- CAT IV safety rating
- Auto power-off
- Convenient pocket clip
- Does not detect DC voltage
- **NCVT-1** provides non-contact detection of standard voltage 50 to 1000V AC in cables, cords, circuit breakers, lighting fixtures, switches, outlets and wires
- **NCVT-2** provides non-contact detection of standard voltage 12 - 1000V AC in cables, cords, circuit breakers, lighting fixtures, switches, outlets and wires. It also detects and indicates low voltage (12 to 40V AC) in security, entertainment, communications, environmental and irrigation systems
- **NCVT-3** features a flashlight, and provides non-contact detection of voltage 12 to 1000V AC with simultaneous visual and audible voltage indicators. US Patent No. D750985
- **NCVT-4IR** is designed for HVAC applications and hot spots in panels, includes an infrared thermometer with selectable °F/°C from -20 to 482°F (-30 to 250°C), LCD backlit display, and convenient laser pointer to help target 4:1 distance to spot ratio for temperature



NCVT-1



NCVT-2



NCVT-3



NCVT-4IR



Features	NCVT-1	NCVT-2	NCVT-3	NCVT-4IR
Drop Protection	9.8 ft. (3 m)	9.8 ft. (3 m)	6.6 ft. (2 m)	6.6 ft. (2 m)
Ingress Protection	IP40	IP40	IP67	IP54
Safety	CAT IV 1000V	CAT IV 1000V	CAT IV 1000V	CAT IV 1000V
Voltage	50-1000V AC	Mode 1: 12-40V AC Mode 2: 12-1000V AC	12-1000V AC	12-1000V AC
Frequency Range	50-500Hz	50-500Hz	50-500Hz	50-500Hz
Audible and Visual Alarms	●	●	●	●
Auto-Power Off	●	●	●	●
Temperature	—	—	—	-22° - 482°F (-30° - 250°C)
Laser	—	—	—	Class 2
Flashlight	—	—	●	—
Backlight	—	—	—	●
LCD Display	—	—	—	●
Batteries	2 x AAA	2 x AAA	2 x AAA	2 x AAA

Cat. No.	Voltage	Frequency	Batteries	Overall Length	Overall Height	Overall Width	Weight
NCVT-1	50 - 1000V AC	50 - 500 Hz	2 x AAA	5.50" (139.7 mm)	1.00" (25.4 mm)	0.72" (18.3 mm)	0.80 oz (22.70 g)
NCVT-2	12 - 1000V AC	50 - 500 Hz	2 x AAA	5.50" (139.7 mm)	1.00" (25.4 mm)	0.72" (18.3 mm)	0.80 oz (22.70 g)
NCVT-3	12 - 1000V AC	50 - 500 Hz	2 x AAA	5.83" (148.0 mm)	1.16" (29.4 mm)	0.72" (18.3 mm)	1.20 oz (34.00 g)
NCVT-4IR	12 - 1000V AC	50 - 500 Hz	2 x AAA	6.25" (158.8 mm)	1.25" (31.8 mm)	1.19" (30.2 mm)	2.00 oz (57.00 g)