



Actual

Catalog Number: EXBBT0710
Product ID: 7TCA297120R0453
EAN Number: 05011949243279
Status: Active

Liquid Tight Metallic Conduit, Low Fire Hazard with EMC Protection, Conduit Size 40mm, Minimum Bore 35.3mm, Reel Length 10 Meters, Galvanized Steel Core with Low Toxicity Covering, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Metallic Conduit
Special Features	Limited Fire Hazard, Zero Halogen (BS6425 Pt1)
Application	Connection for Conduit Systems when Low Fire Hazard is Needed
Standard	LUL compliant (E1042A6)
Trade Size	40mm
Inside Diameter	35.3mm
Length	10 Meters
Material	Galvanized Steel Core with Low Toxicity Covering
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	40mm
Nominal size in inch	1 1/4 inch
Inner diameter	35.3mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	Megolon, flame retardant
Operating temperature	-25-+90°C
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23 Y	

Packaging

Outer Quantity	1
Outer Dimensions (inches)	12x14x12
Weight Uom	21.31 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com