

Catalog Number: EXLB0810
Product ID: 7TCA297120R0080
EAN Number: 05011949001701
Status: Active



Actual

Liquid Tight Metallic Conduit, Oil and Dilute Acid Resistant, Conduit Size 50mm, Minimum Bore 40.4mm, Reel Length 10 Meters, Galvanised Steel Core with Flame Retardant PVC Covering, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Metallic Conduit
Special Features	Flame Retardant PVC Covering
Application	Connection for Conduit Systems when Oil and Acid Resistance is Needed
Standard	IEC 61386
Trade Size	50mm
Inside Diameter	40.4mm
Length	10 Meters
Material	Galvanized Steel Core with Flame Retardant PVC Covering
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	50mm
Nominal size in inch	1 1/2 inch
Inner diameter	40.4mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	PVC, flame retardant
Operating temperature	-20-+70°C
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23 Y	

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	32.82 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com