


Catalog Number: EXLT0620
Product ID: 7TCA297120R0141
EAN Number: 05011949001251
Status: Active

Liquid Tight Metallic Conduit, Low Fire Hazard, Conduit Size 32mm, Minimum Bore 26.4mm, Reel Length 20 Meters, Galvanised Steel Core with LFH Coating, Black



Actual

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Metallic Conduit
Special Features	Limited Fire Hazard, Zero Halogen (BS6425 Pt1)
Application	Connection for Conduit Systems when Low Fire Hazard is Needed
Standard	LUL compliant (E1042A6)
Trade Size	32mm
Inside Diameter	26.4mm
Length	20 Meters
Material	Galvanized Steel Core with Low Fire Hazard Coating
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	32mm
Nominal size in inch	1 inch
Material	Steel
Surface protection	Untreated
Sheathing material 1st coating	Megolon, flame retardant
Operating temperature	-20-+70°C
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23 Y	

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	34.09 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com