

Catalog Number: EXLUB0310
Product ID: 7TCA297120R0424
EAN Number: 05011949241114
Status: Active

Liquid Tight, Pliable Conduit, Nominal Conduit Size 16mm, 3/8 Inch US Trade Size, Inside Diameter 12.5mm, UL E76358, Approved to EN/IEC 60079-0, 60079-7, 60079-31 UL360, Static Bend Radius 50mm, Reel Length 10 Meters, Galvanized Steel Core with PVC Covering and Copper Grounding Wire, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Flame Retardant Conduit
Application	Can Be Used with Ex LT Fittings for Ex E Systems or Combination Ex LT and HA-G1 Fittings for Ex D E Systems
Standard	UL E76358, Approved to EN/IEC 60079-0, 60079-7, 60079-31 UL360
Trade Size	NC 16mm/3/8 Inch
Inside Diameter	12.5mm
Length	10 Meters
Radius	50mm
Flexibility	Pliable
Material	Galvanized Steel Core and Copper Grounding Wire with PVC Covering
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	16mm
Nominal size in inch	3/8 inch
Inner diameter	12.5mm
Material	Steel
Surface protection	Other
Sheathing material 1st coating	PVC
Operating temperature	-20-+70°C
Colour	Black
Bending strength	Pliable
With approval according to UL	Y

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	10.42 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com