

Catalog Number: EXSA0505
Product ID: 7TCA297120R0243
EAN Number: 05011949018259
Status: Active

Connector for Liquid Tight Conduit, 90 Degree Bend, Conduit Size 3/4 Inch/25mm, Thread Size 3/4 Inch NPT, For Use in Industrial and Zone 2 Applications, IP66-67 Rating, Nickel Plated Brass

North American Specifications (UNSPSC)

UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	Kopex
Type	90 Degree Connector for Liquid Tight Conduit
Application	For Use in Industrial and Zone 2 Applications to Connect Conduit Systems
Standard	BS EN 61386
Size	Conduit Size 25mm/3/4 Inch
Connection	90 Degree 3/4 Inch NPT Thread
Material	Brass
Finish	Nickel Plated
Color	Metallic
Insulation	IP66, 67 Rating
Temperature Rating	-50 to 130 Degree C
Environmental Conditions	Industrial and Zone 2 Areas

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal diameter	25mm
Nominal size in inch	3/4 inch
Degree of protection (IP) conduit dependant	IP66-IP67
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Thread type	NPT
Thread connection size	Other
One-piece	Y
Material housing	Brass
Surface protection	Nickel-plated
Total length	63.7mm
Approved in combination with protective conduit DIN EN 61386-23	Y
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UL	N
Approved in combination with protective conduit FI	N
Operating temperature	-20-+70°C

Packaging

Inner Quantity	2
Outer Quantity	10
Outer Dimensions (inches)	1x1x1
Weight Uom	0.42 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com