

Catalog Number: EXSB0430
Product ID: 7TCA297120R0251
EAN Number: 05011949002067
Status: Active



Actual

Liquid Tight Metallic Conduit, Oil and Dilute Acid Resistant, Conduit Size 20mm, Minimum Bore 16mm, Reel Length 30 Meters, 316 Stainless Steel Core with Flame Retardant PVC Covering, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Metallic Conduit
Special Features	Flame Retardant PVC Covering
Application	Connection for Conduit Systems when Oil and Acid Resistance is Needed
Standard	IEC 61386
Trade Size	20mm
Inside Diameter	16mm
Length	30 Meters
Material	316 Stainless Steel Core with Flame Retardant PVC Covering
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	20mm
Nominal size in inch	1/2 inch
Inner diameter	16mm
Material	Stainless steel
Surface protection	Untreated
Sheathing material 1st coating	PVC, flame retardant
Operating temperature	-20-+70°C
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23 Y	

Packaging

Inner Quantity	1
Inner Dimensions (inches)	11x14x11
Outer Quantity	1
Outer Dimensions (inches)	12x13x13
Weight Uom	23.06 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com