



Actual

Catalog Number: EXSHC0610
Product ID: 7TCA297120R0284
EAN Number: 05011949231214
Status: Active

Liquid Tight Metallic Conduit, Highly Flexible, High Temperature Applications, Conduit Size 32mm, Minimum Bore 26.4mm, Reel Length 10 Meters, Stainless Steel Core with Thermoplastic Rubber Coating, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5543 Liquid Tight Conduit
Brand Name	Kopex
Type	Liquid Tight Metallic Conduit
Application	Connection for Conduit Systems with High Temperature Applications
Standard	IEC61386
Trade Size	32mm
Inside Diameter	26.4mm
Length	10 Meters
Material	Stainless Steel Core and Thermoplastic Rubber Coating
Color	Black

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	32mm
Nominal size in inch	1 inch
Inner diameter	26.4mm
Material	Stainless steel
Surface protection	Untreated
Sheathing material 1st coating	Other
Operating temperature	-35-+105°C
Colour	Black
Bending strength	Flexible
Approved according to DIN EN 61386-23 Y	

Packaging

Outer Quantity	1
Outer Dimensions (inches)	14x14x6
Weight Uom	1 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com